

Package ‘PFIM’

October 23, 2024

Type Package

Title Population Fisher Information Matrix

Version 6.1

NeedsCompilation no

Description Evaluate or optimize designs for nonlinear mixed effects models using the Fisher Information matrix. Methods used in the package refer to
Mentré F, Mallet A, Baccar D (1997) <[doi:10.1093/biomet/84.2.429](https://doi.org/10.1093/biomet/84.2.429)>,
Retout S, Comets E, Samson A, Mentré F (2007) <[doi:10.1002/sim.2910](https://doi.org/10.1002/sim.2910)>,
Bazzoli C, Retout S, Mentré F (2009) <[doi:10.1002/sim.3573](https://doi.org/10.1002/sim.3573)>,
Le Nagard H, Chao L, Tenaillon O (2011) <[doi:10.1186/1471-2148-11-326](https://doi.org/10.1186/1471-2148-11-326)>,
Combes FP, Retout S, Frey N, Mentré F (2013) <[doi:10.1007/s11095-013-1079-3](https://doi.org/10.1007/s11095-013-1079-3)> and
Seurat J, Tang Y, Mentré F, Nguyen TT (2021) <[doi:10.1016/j.cmpb.2021.106126](https://doi.org/10.1016/j.cmpb.2021.106126)>.

URL <http://www.pfim.biostat.fr/>

Depends R (>= 4.0.0)

License GPL (>= 2)

Encoding UTF-8

Imports inline, utils, methods, deSolve, Deriv, scales, devtools,
ggplot2, Matrix, pracma, stringr, Rcpp, knitr, purrr,
rmarkdown, kableExtra, stats

RoxygenNote 7.3.2

VignetteBuilder knitr

Collate 'GenericMethods.R' 'Administration.R'
'AdministrationConstraints.R' 'Arm.R' 'Fim.R' 'BayesianFim.R'
'ModelError.R' 'Combined1.R' 'Constant.R' 'Design.R'
'Distribution.R' 'ModelParameter.R' 'LibraryOfPDMModels.R'
'LibraryOfPKModels.R' 'LibraryOfModels.R'
'LibraryOfPKPDMModels.R' 'Model.R' 'PFIMProject.R'
'Evaluation.R' 'OptimizationAlgorithm.R'
'FedorovWynnAlgorithm.R' 'IndividualFim.R' 'LogNormal.R'
'ModelODE.R' 'ModelAnalytic.R' 'ModelAnalyticBolus.R'
'ModelAnalyticSteadyState.R' 'ModelAnalyticBolusSteadyState.R'
'ModelInfusion.R' 'ModelAnalyticInfusion.R'

'ModelAnalyticInfusionSteadyState.R' 'ModelBolus.R'
 'ModelODEBolus.R' 'ModelODEDoseInEquations.R'
 'ModelODEDoseNotInEquations.R' 'ModelODEInfusion.R'
 'ModelODEInfusionDoseInEquations.R' 'MultiplicativeAlgorithm.R'
 'Normal.R' 'Optimization.R' 'PFIM-package.R' 'PGBOAlgorithm.R'
 'PSOAlgorithm.R' 'PlotEvaluation.R' 'PopulationFim.R'
 'Proportional.R' 'SamplingTimeConstraints.R' 'SamplingTimes.R'
 'SimplexAlgorithm.R'

Author France Mentré [aut],
 Romain Leroux [aut, cre],
 Jérémy Seurat [aut],
 Lucie Fayette [aut]

Maintainer Romain Leroux <romain.leroux@inserm.fr>

Repository CRAN

Date/Publication 2024-10-23 17:00:06 UTC

Contents

PFIM-package	8
addModel	21
addModels	21
Administration-class	22
AdministrationConstraints-class	22
Arm-class	23
BayesianFim-class	23
checkSamplingTimeConstraintsForContinuousOptimization	23
checkValiditySamplingConstraint	24
Combined1-class	25
computeVMat	25
Constant-class	26
convertPKModelAnalyticToPKModelODE	26
dataForArmEvaluation	27
defineModel	27
defineModelEquationsFromStringToFunction	28
defineModelFromLibraryOfModels	30
defineModelType	30
defineModelUserDefined	31
definePKModel	31
definePKPDMModel	32
Design-class	33
Distribution-class	34
EvaluateArm	34
EvaluateDesign	35
EvaluateErrorModelDerivatives	35
EvaluateFisherMatrix	36
EvaluateModel	37

EvaluateModelGradient	38
EvaluateVarianceFIM	39
EvaluateVarianceModel	39
Evaluation-class	40
FedorovWynnAlgorithm-class	41
FedorovWynnAlgorithm_Rcpp	41
Fim-class	42
fisher.simplex	43
fun.amoeba	43
generateFimsFromConstraints	44
generateReportEvaluation	44
generateReportOptimization	46
generateSamplingsFromSamplingConstraints	47
generateTables	48
getAdjustedGradient	48
getAdministration	49
getAdministrationConstraint	49
getAdministrations	50
getAdministrationsConstraints	50
getArms	51
getError	51
getColumnAndParametersNamesFIM	52
getColumnAndParametersNamesFIMInLatex	53
getConditionNumberFixedEffects	53
getConditionNumberVarianceEffects	54
getContent	54
getCorrelationMatrix	55
getDataForArmEvaluation	55
getDataFrameResults	56
getDcriterion	57
getDelta	57
getDerivatives	58
getDescription	58
getDesigns	59
getDeterminant	59
getDistribution	60
getDose	60
getEigenValues	61
getElementaryProtocols	61
getEquation	62
getEquations	62
getEquationsAfterInfusion	63
getEquationsDuringInfusion	63
getEvaluationFIMResults	64
getEvaluationInitialDesignResults	64
getFim	65
getFisherMatrix	65
getFixedEffects	66

getFixedMu	66
getFixedOmega	67
getFixedParameters	67
getFixedTimes	68
getInitialConditions	68
getIterationAndCriteria	69
getLambda	69
getLibraryPDMODELS	70
getLibraryPKMODELS	70
getMinSampling	71
getModel	71
getModelEquations	72
getModelError	72
getModelErrorParametersValues	73
getModelFromLibrary	73
getModelParameters	74
getModelParametersValues	74
getMu	75
getName	75
getNames	76
getNumberOfArms	77
getNumberOfIterations	77
getNumberOfParameters	78
getNumberOfSamplingsOptimisable	78
getNumberOfTimesByWindows	79
getOdeSolverParameters	79
getOmega	80
getOptimalDesign	80
getOptimalFrequencies	81
getOptimalWeights	81
getOptimizationResults	82
getOptimizer	82
getOptimizerParameters	83
getOutcome	83
getOutcomes	84
getOutcomesEvaluation	84
getOutcomesForEvaluation	85
getOutcomesGradient	85
getParameters	86
getPDMODEL	87
getPKMODEL	87
getPKPDMODEL	88
getPlotOptions	88
getProportionsOfSubjects	89
getRSE	89
getSamplings	90
getSamplingsWindows	90
getSamplingTime	91

getSamplingTimeConstraint	91
getSamplingTimes	92
getSamplingTimesConstraints	92
getSE	93
getShrinkage	93
getSigmaInter	94
getSigmaSlope	95
getSize	95
getTau	96
getTimeDose	96
getTinf	97
getVariables	97
getVarianceEffects	98
getWeightThreshold	98
IndividualFim-class	99
initialize,Administration-method	99
initialize,AdministrationConstraints-method	100
initialize,Arm-method	100
initialize,Combined1-method	101
initialize,Constant-method	102
initialize,Design-method	103
initialize,Distribution-method	104
initialize,Evaluation-method	104
initialize,FedorovWynnAlgorithm-method	105
initialize,Fim-method	106
initialize,LibraryOfModels-method	106
initialize,LibraryOfPKPDMODELS-method	107
initialize,LogNormal-method	107
initialize,Model-method	108
initialize,ModelAnalytic-method	109
initialize,ModelAnalyticBolus-method	109
initialize,ModelAnalyticBolusSteadyState-method	110
initialize,ModelAnalyticInfusion-method	111
initialize,ModelAnalyticInfusionSteadyState-method	112
initialize,ModelAnalyticSteadyState-method	113
initialize,ModelBolus-method	113
initialize,ModelError-method	114
initialize,ModelInfusion-method	115
initialize,ModelParameter-method	116
initialize,MultiplicativeAlgorithm-method	117
initialize,Normal-method	118
initialize,Optimization-method	118
initialize,OptimizationAlgorithm-method	119
initialize,PFIMProject-method	120
initialize,PGBOAlgorithm-method	120
initialize,Proportional-method	121
initialize,PSOAlgorithm-method	122
initialize,SamplingTimeConstraints-method	123

initialize,SamplingTimes-method	124
initialize,SimplexAlgorithm-method	125
isDoseInEquations	126
isModelAnalytic	126
isModelBolus	127
isModelInfusion	127
isModelODE	128
isModelSteadyState	128
LibraryOfModels-class	129
LibraryOfPDMModels	129
LibraryOfPKModels	129
LibraryOfPKPDMModels-class	130
LogNormal-class	130
Model-class	130
ModelAnalytic-class	131
ModelAnalyticBolus-class	131
ModelAnalyticBolusSteadyState-class	131
ModelAnalyticInfusion-class	131
ModelAnalyticInfusionSteadyState-class	132
ModelAnalyticSteadyState-class	132
ModelBolus-class	132
ModelError-class	132
ModelInfusion-class	132
ModelODE-class	133
ModelODEDoseInEquations-class	133
ModelODEDoseNotInEquations-class	133
ModelODEInfusion-class	133
ModelODEInfusionDoseInEquations-class	134
ModelParameter-class	134
MultiplicativeAlgorithm-class	134
MultiplicativeAlgorithm_Rcpp	135
Normal-class	136
Optimization-class	136
OptimizationAlgorithm-class	137
optimize	137
parametersForComputingGradient	138
PFIMProject-class	139
PGBOAlgorithm-class	139
plotEvaluation	140
PlotEvaluation-class	140
plotFrequencies	140
plotOutcomesEvaluation	141
plotOutcomesGradient	142
plotRSE	142
plotSE	143
plotSensitivityIndice	143
plotShrinkage	144
plotWeights	144

PopulationFim-class	145
Proportional-class	145
PSOAlgorithm-class	146
Report	146
reportTablesAdministration	147
reportTablesDesign	147
reportTablesFIM	148
reportTablesModelError	149
reportTablesModelParameters	149
reportTablesPlot	150
reportTablesSamplingConstraints	150
resizeFisherMatrix	151
run	151
SamplingTimeConstraints-class	152
SamplingTimes-class	152
setAdministrations	153
setArm	153
setArms	154
setcError	154
setContent	155
setDataForArmEvaluation	155
setDataForModelEvaluation	156
setDerivatives	157
setDescription	157
setDesigns	158
setDistribution	158
setDose	159
setEquation	159
setEquations	160
setEquationsAfterInfusion	160
setEquationsDuringInfusion	161
setEvaluationFIMResults	161
setEvaluationInitialDesignResults	162
setFim	162
setFimTypeToString	163
setFisherMatrix	163
setFixedEffects	164
setFixedMu	164
setFixedOmega	165
setInitialConditions	165
setIterationAndCriteria	166
setModel	166
setModelError	167
setModelFromLibrary	167
setMu	168
setName	168
setNumberOfArms	169
setOdeSolverParameters	169

setOmega	170
setOptimalDesign	171
setOptimalWeights	171
setOptimizationResults	172
setOutcome	172
setOutcomes	173
setOutcomesEvaluation	173
setOutcomesForEvaluation	174
setOutcomesGradient	174
setParameters	175
setSamplingConstraintForOptimization	176
setSamplings	176
setSamplingTime	177
setSamplingTimes	177
setSamplingTimesConstraints	178
setShrinkage	178
setSigmaInter	179
setSigmaSlope	179
setSize	180
setTau	181
setTimeDose	181
setTinf	182
setVarianceEffects	182
show,Design-method	183
SimplexAlgorithm-class	184

Index**185**

PFIM-package	<i>Fisher Information matrix for design evaluation/optimization for non-linear mixed effects models.</i>
--------------	--

Description

Evaluate or optimize designs for nonlinear mixed effects models using the Fisher Information matrix. Methods used in the package refer to Mentré F, Mallet A, Baccar D (1997) doi: [10.1093/biomet/84.2.429](https://doi.org/10.1093/biomet/84.2.429), Retout S, Comets E, Samson A, Mentré F (2007) doi: [10.1002/sim.2910](https://doi.org/10.1002/sim.2910), Bazzoli C, Retout S, Mentré F (2009) doi: [10.1002/sim.3573](https://doi.org/10.1002/sim.3573), Le Nagard H, Chao L, Tenaillon O (2011) doi: [10.1186/1471214811326](https://doi.org/10.1186/1471214811326), Combes FP, Retout S, Frey N, Mentré F (2013) doi: [10.1007/s11095-01310793](https://doi.org/10.1007/s11095-01310793) and Seurat J, Tang Y, Mentré F, Nguyen TT (2021) doi: [10.1016/j.cmpb.2021.106126](https://doi.org/10.1016/j.cmpb.2021.106126).

Description

Nonlinear mixed effects models (NLMEM) are widely used in model-based drug development and use to analyze longitudinal data. The use of the "population" Fisher Information Matrix (FIM) is a good alternative to clinical trial simulation to optimize the design of these studies. The present version, **PFIM** 6.1, is an R package that uses the S4 object system for evaluating and/or optimizing population designs based on FIM in NLMEMs.

This version of **PFIM** now includes a library of models implemented also using the object oriented system S4 of R. This library contains two libraries of pharmacokinetic (PK) and/or pharmacodynamic (PD) models. The PK library includes model with different administration routes (bolus, infusion, first-order absorption), different number of compartments (from 1 to 3), and different types of eliminations (linear or Michaelis-Menten). The PD model library, contains direct immediate models (e.g. Emax and I_{max}) with various baseline models, and turnover response models. The PK/PD models are obtained with combination of the models from the PK and PD model libraries. **PFIM** handles both analytical and ODE models and offers the possibility to the user to define his/her own model(s). In **PFIM 6.1**, the FIM is evaluated by first order linearization of the model assuming a block diagonal FIM as in [3]. The Bayesian FIM is also available to give shrinkage predictions [4]. **PFIM 6.1** includes several algorithms to conduct design optimization based on the D-criterion, given design constraints : the simplex algorithm (Nelder-Mead) [5], the multiplicative algorithm [6], the Fedorov-Wynn algorithm [7], PSO (*Particle Swarm Optimization*) and PGBO (*Population Genetics Based Optimizer*) [9].

Documentation

Documentation and user guide are available at <http://www.pfim.biostat.fr/>

Validation

PFIM 6.1 also provides quality control with tests and validation using the evaluated FIM to assess the validity of the new version and its new features. Finally, **PFIM 6.1** displays all the results with both clear graphical form and a data summary, while ensuring their easy manipulation in R. The standard data visualization package ggplot2 for R is used to display all the results with clear graphical form [10]. A quality control using the D-criterion is also provided.

Organization of the source files in the /R folder

PFIM 6.1 contains a hierarchy of S4 classes with corresponding methods and functions serving as constructors. All of the source code related to the specification of a certain class is contained in a file named [Name_of_the_class]-Class.R. These classes include:

- 1. all roxygen @include to insure the correctly generated collate for the DESCRIPTION file,
- 2. \setClass preceded by a roxygen documentation that describes the purpose and slots of the class,
- 3. specification of an initialize method,
- 4. all getter and setter, respectively returning attributes of the object and associated objects.

Content of the source code and files in the /R folder

Class `Administration`

- `getOutcome`
- `setOutcome`
- `getTimeDose`
- `setTimeDose`
- `getDose`

- setDose
- getTinf
- setTinf
- getTau
- setTau

Class AdministrationConstraints

- getOutcome
- getDose

Class Arm

- getName
- setName
- getSize
- setSize
- getAdministrations
- setAdministrations
- getSamplingTimes
- setSamplingTimes
- getInitialConditions
- setInitialConditions
- getAdministrationsConstraints
- getSamplingTimesConstraints
- getSamplingTime
- getSamplingTimeConstraint
- setSamplingTimesConstraints
- setSamplingTime
- getAdministration
- getAdministrationConstraint
- EvaluateArm

Class BayesianFim

- EvaluateFisherMatrix
- getRSE
- getConditionNumberVarianceEffects
- getShrinkage
- setShrinkage
- reportTablesFIM

- [generateReportEvaluation](#)

Class [Combined1](#)

- See class [ModelError](#)

Class [Constant](#)

- See class [ModelError](#)

Class [Design](#)

- [getName](#)
- [setName](#)
- [getSize](#)
- [setSize](#)
- [setArms](#)
- [getOutcomesEvaluation](#)
- [setOutcomesEvaluation](#)
- [getOutcomesGradient](#)
- [setOutcomesGradient](#)
- [getFim](#)
- [setFim](#)
- [getNumberOfArms](#)
- [setNumberOfArms](#)
- [setArm](#)
- [EvaluateDesign](#)
- [plotOutcomesEvaluation](#)
- [plotOutcomesGradient](#)
- [reportTablesAdministration](#)
- [reportTablesDesign](#)

Class [Distribution](#)

- [getParameters](#)
- [setParameters](#)
- [getMu](#)
- [setMu](#)
- [getOmega](#)
- [setOmega](#)
- [getAdjustedGradient](#)

Class [Evaluation](#)

- run
- reportTablesPlot
- generateTables
- Report

Class FedorovWynnAlgorithm

- FedorovWynnAlgorithm_Rcpp
- resizeFisherMatrix
- setParameters
- optimize
- generateReportOptimization

Class FedorovWynnAlgorithm

- FedorovWynnAlgorithm_Rcpp
- resizeFisherMatrix
- setParameters
- optimize
- generateReportOptimization

Class Fim

- EvaluateFisherMatrix
- EvaluateVarianceFIM
- getFisherMatrix
- setFisherMatrix
- getFixedEffects
- setFixedEffects
- getVarianceEffects
- setVarianceEffects
- getDeterminant
- getDcriterion
- getCorrelationMatrix
- getSE
- getRSE
- getShrinkage
- getEigenValues
- getConditionNumberFixedEffects
- getConditionNumberVarianceEffects
- getColumnAndParametersNamesFIM

- getColumnAndParametersNamesFIMInLatex
- reportTablesFIM
- generateReportEvaluation
- setFimTypeToString

Class GenericMethods

- getName
- getNames
- getSize
- setSize
- getOutcome
- setOutcome
- getFim
- getOdeSolverParameters
- getMu
- setMu
- getOmega
- setOmega
- getParameters
- setParameters
- getModelError
- getSamplings
- getFim
- setName
- setArms
- getArms

Class IndividualFim

- EvaluateFisherMatrix
- EvaluateVarianceFIM
- getRSE
- getShrinkage
- setShrinkage
- reportTablesFIM
- generateReportEvaluation

Class LibraryOfModels

- getName

- `getContent`
- `setContent`
- `addModel`
- `addModels`
- `getLibraryPKModels`
- `getLibraryPDMModels`

Class `LibraryOfPKPDMModels`

- `getPKModel`
- `getPDMModel`
- `getPKPDMModel`

Class `LogNormal`

- `getAdjustedGradient`

Class `Model`

- `getName`
- `setName`
- `getDescription`
- `setDescription`
- `getEquations`
- `setEquations`
- `setModelFromLibrary`
- `getOutcomes`
- `setOutcomes`
- `getOutcomesForEvaluation`
- `setOutcomesForEvaluation`
- `getParameters`
- `setParameters`
- `getModelError`
- `setModelError`
- `getInitialConditions`
- `setInitialConditions`
- `getOdeSolverParameters`
- `setOdeSolverParameters`
- `getModelFromLibrary`
- `convertPKModelAnalyticToPKModelODE`
- `getNumberOfParameters`

- `isModelODE`
- `isModelAnalytic`
- `isDoseInEquations`
- `isModelInfusion`
- `isModelSteadyState`
- `isModelBolus`
- `definePKPDMModel`
- `definePKModel`
- `defineModel`
- `defineModelFromLibraryOfModels`
- `defineModelUserDefined`
- `defineModelType`
- `EvaluateModel`
- `parametersForComputingGradient`
- `EvaluateVarianceModel`
- `getFixedParameters`
- `getModelErrorParametersValues`
- `reportTablesModelParameters`
- `reportTablesModelError`

Class `ModelAnalytic`

- `EvaluateModel`
- `definePKModel`
- `definePKPDMModel`
- `convertPKModelAnalyticToPKModelODE`

Class `ModelAnalyticBolus`

- See class `ModelAnalytic`

Class `ModelAnalyticBolusSteadyState`

- See class `ModelAnalyticBolus`

Class `ModelBolus`

- See class `Model`

Class `ModelError`

- `getOutcome`
- `getEquation`

- `setEquation`
- `getDerivatives`
- `setDerivatives`
- `getSigmaInter`
- `setSigmaInter`
- `getSigmaSlope`
- `setSigmaSlope`
- `getError`
- `setError`
- `getParameters`
- `EvaluateErrorModelDerivatives`

Class `ModelInfusion`

- `getEquationsDuringInfusion`
- `getEquationsAfterInfusion`
- `setEquationsAfterInfusion`
- `setEquationsDuringInfusion`

Class `ModelODE`

- See class `Model`

Class `ModelODEBolus`

- `EvaluateModel`
- `definePKPDMModel`

Class `ModelODEDoseInEquations`

- `EvaluateModel`
- `definePKModel`
- `definePKPDMModel`

Class `ModelODEDoseNotInEquations`

- `EvaluateModel`
- `definePKModel`
- `definePKPDMModel`

Class `ModelODEInfusion`

- See class `ModelInfusion`

Class `ModelODEInfusionDoseInEquations`

- EvaluateModel
- definePKModel
- definePKPDMModel

Class ModelParameter

- getName
- getDistribution
- setDistribution
- getFixedMu
- setFixedMu
- getFixedOmega
- setFixedOmega
- getMu
- setMu
- getOmega
- setOmega

Class MultiplicativeAlgorithm

- MultiplicativeAlgorithm_Rcpp
- getLambda
- getDelta
- getNumberOfIterations
- getOptimalWeights
- setOptimalWeights
- setParameters
- optimize
- getDataFrameResults
- plotWeights
- getWeightThreshold
- generateReportOptimization

Class Normal

- getAdjustedGradient

Class Optimization

- getProportionsOfSubjects
- getOptimizationResults
- setOptimizationResults

- `getEvaluationFIMResults`
- `setEvaluationFIMResults`
- `setEvaluationInitialDesignResults`
- `getEvaluationInitialDesignResults`
- `getElementaryProtocols`
- `generateFimsFromConstraints`
- `run`
- `plotWeights`
- `Report`

Class `PFIMProject`

- `getName`
- `setModel`
- `getModel`
- `getModelEquations`
- `getModelParameters`
- `getModelError`
- `getDesigns`
- `getFim`
- `getOdeSolverParameters`
- `getOutcomes`
- `getOptimizer`
- `getOptimizerParameters`
- `run`
- `generateTables`
- `Report`

Class `PGB0Algorithm`

- `setParameters`
- `optimize`
- `generateReportOptimization`

Class `PlotEvaluation`

- `plot`
- `plotSE`
- `plotRSE`
- `plotShrinkage`

Class `PopulationFim`

- EvaluateFisherMatrix
- EvaluateVarianceFIM
- getRSE
- getShrinkage
- setShrinkage
- reportTablesFIM
- computeVMat
- generateReportEvaluation

Class Proportional

- See class ModelError

Class PSOAlgorithm

- setParameters
- optimize
- generateReportOptimization

Class SamplingTimeConstraints

- getOutcome
- getSamplings
- getFixedTimes
- getNumberOfTimesByWindows
- getMinSampling
- getSamplingsWindows
- getNumberOfSamplingsOptimisable
- checkSamplingTimeConstraintsForContinuousOptimization
- generateSamplingsFromSamplingConstraints

Class SamplingTimes

- getOutcome
- setOutcome
- getSamplings
- setSamplings

Class SimplexAlgorithm

- setParameters
- fun.amoeba
- fisher.simplex
- optimize
- generateReportOptimization

Author(s)

Maintainer: Romain Leroux <romain.leroux@inserm.fr>

Authors:

- France Mentré <france.mentre@inserm.fr>
- Jérémy Seurat <jeremy.seurat@inserm.fr>
- Lucie Fayette <lucie.fayette@inserm.fr>

References

- [1] Dumont C, Lestini G, Le Nagard H, Mentré F, Comets E, Nguyen TT, et al. PFIM 4.0, an extended R program for design evaluation and optimization in nonlinear mixed-effect models. *Comput Methods Programs Biomed.* 2018;156:217-29.
- [2] Chambers JM. Object-Oriented Programming, Functional Programming and R. *Stat Sci.* 2014;29:167-80.
- [3] Mentré F, Mallet A, Baccar D. Optimal Design in Random-Effects Regression Models. *Biometrika.* 1997;84:429-42.
- [4] Combes FP, Retout S, Frey N, Mentré F. Prediction of shrinkage of individual parameters using the Bayesian information matrix in nonlinear mixed effect models with evaluation in pharmacokinetics. *Pharm Res.* 2013;30:2355-67.
- [5] Nelder JA, Mead R. A simplex method for function minimization. *Comput J.* 1965;7:308-13.
- [6] Seurat J, Tang Y, Mentré F, Nguyen, TT. Finding optimal design in nonlinear mixed effect models using multiplicative algorithms. *Computer Methods and Programs in Biomedicine*, 2021.
- [7] Fedorov VV. *Theory of Optimal Experiments.* Academic Press, New York, 1972.
- [8] Eberhart RC, Kennedy J. A new optimizer using particle swarm theory. *Proc. of the Sixth International Symposium on Micro Machine and Human Science, Nagoya, 4-6 October 1995*, 39-43.
- [9] Le Nagard H, Chao L, Tenaillon O. The emergence of complexity and restricted pleiotropy in adapting networks. *BMC Evol Biol.* 2011;11:326.
- [10] Wickham H. *ggplot2: Elegant Graphics for Data Analysis*, Springer-Verlag New York, 2016.

See Also

Useful links:

- <http://www.pfim.biostat.fr/>

addModel	<i>Add a model to a library of models.</i>
----------	--

Description

Add a model to a library of models.

Usage

```
addModel(object, model)
```

```
## S4 method for signature 'LibraryOfModels'  
addModel(object, model)
```

Arguments

object	An object from the class LibraryOfModels .
model	An object from the class Model .

Value

The library of models with the added model.

addModels	<i>Add a models to a library of models.</i>
-----------	---

Description

Add a models to a library of models.

Usage

```
addModels(object, models)
```

```
## S4 method for signature 'LibraryOfModels'  
addModels(object, models)
```

Arguments

object	An object from the class LibraryOfModels .
models	A list of object from the class Model .

Value

The library of models with the added models.

Administration-class *Class "Administration"*

Description

The class Administration defines information concerning the parametrization and the type of administration: single dose, multiple doses. Constraints can also be added on the allowed times, doses and infusion duration.

Objects from the class

Objects from the class Administration can be created by calls of the form Administration(...) where (...) are the parameters for the Administration objects.

Slots for Administration objects

outcome: A character string giving the name for the response of the model.

timeDose: A numeric vector giving the times when doses are given.

dose: A numeric vector giving the amount of doses.

Tinf: A numeric vector giving the infusion duration Tinf (Tinf can be null).

tau: A numeric giving the frequency.

AdministrationConstraints-class
 Class "AdministrationConstraints"

Description

The class AdministrationConstraints represents the constraint of an input to the system. The class stores information concerning the constraints for the dosage regimen: response of the model, amount of dose.

Objects from the class

Objects from the class AdministrationConstraints can be created by calls of the form AdministrationConstraints(...) where (...) are the parameters for the AdministrationConstraints objects.

Slots for AdministrationConstraints objects

outcome: A character string giving the name for the response of the model.

doses: A numeric vector giving the amount of doses.

 Arm-class

 Class "Arm"

Description

The class Arm combines the treatment and the sampling schedule.

Objects from the class

Objects from the class Arm can be created by calls of the form Arm(. . .) where (...) are the parameters for the Arm objects.

Slots for the Arm objects

name: A string giving the name of the arm.

size: An integer giving the number of subjects in the arm. By default set to 1.

administrations: A list of the administrations.

initialConditions: A list of the initial conditions.

samplingTimes: A list of the sampling times.

administrationsConstraints: A list of the administrations constraints.

samplingTimesConstraints: A list of the sampling times constraints.

 BayesianFim-class

 Class "BayesianFim"

Description

The class BayesianFim represents the population Fisher information matrix. The class BayesianFim inherits from the class Fim.

 checkSamplingTimeConstraintsForContinuousOptimization

Check for the samplingTime constraints for continuous optimization

Description

Check for the samplingTime constraints for continuous optimization

Usage

```

checkSamplingTimeConstraintsForContinuousOptimization(
  object,
  arm,
  newSamplings,
  outcome
)

## S4 method for signature 'SamplingTimeConstraints'
checkSamplingTimeConstraintsForContinuousOptimization(
  object,
  arm,
  newSamplings,
  outcome
)

```

Arguments

object	An object from the class SamplingTimeConstraints .
arm	An object from the class Arm .
newSamplings	A vector giving the new sampling.
outcome	The outcomes for the model.

Value

A list of Boolean giving true if the minimal sampling times is in the vector of sampling times & the number of sampling for each windows is respected false otherwise.

```

checkValiditySamplingConstraint
  checkValiditySamplingConstraint

```

Description

Check the validity of he sampling times constraints

Usage

```

checkValiditySamplingConstraint(object)

## S4 method for signature 'Design'
checkValiditySamplingConstraint(object)

```

Arguments

object	An object from the class Design .
--------	---

Value

An error message if a constraint is not valid.

Combined1-class	Class "Combined1"
-----------------	-------------------

Description

The class Combined1 defines the the residual error variance according to the formula $g(\text{sigmaInter}, \text{sigmaSlope}, \text{cError}, f(x, \text{theta})) = \text{sigmaInter} + \text{sigmaSlope} * f(x, \text{theta})$. The class Combined1 inherits from the class ModelError.

Objects from the class

Combined1 objects are typically created by calls to Combined1 and contain the following slots that are inherited from the class [ModelError](#):

outcome: A string giving the name of the outcome.

equation: An symbolic expression of the model error.

derivatives: A list containing the derivatives of the model error expression.

sigmaInter: A numeric value giving the sigma inter of the error model.

sigmaSlope: A numeric value giving the sigma slope of the error model.

cError: A numeric value giving the exponant c of the error model.

computeVMat	<i>function computeVMat</i>
-------------	-----------------------------

Description

function computeVMat

Usage

```
computeVMat(varParam1, varParam2, invCholV)
```

Arguments

varParam1	varParam1
-----------	-----------

varParam2	varParam2
-----------	-----------

invCholV	invCholV
----------	----------

Value

VMat

Constant-class	Class "Constant"
----------------	------------------

Description

The class Constant defines the the residual error variance according to the formula $g(\text{sigma_inter}, \text{sigma_slope}, \text{c_error}, f(x, \text{theta})) = \text{sigma_inter}$. The class Constant inherits from the class ModelError.

Objects from the class

Constant objects are typically created by calls to Constant and contain the following slots that are inherited from the class ModelError:

outcome: A string giving the name of the outcome.

equation: An symbolic expression of the model error.

derivatives: A list containing the derivatives of the model error expression.

sigmaInter: A numeric value giving the sigma inter of the error model.

sigmaSlope: A numeric value giving the sigma slope of the error model.

cError: A numeric value giving the exponent c of the error model.

convertPKModelAnalyticToPKModelODE	<i>Convert an analytic model to a ode model.</i>
------------------------------------	--

Description

Convert an analytic model to a ode model.

Usage

```
convertPKModelAnalyticToPKModelODE(object)
```

```
## S4 method for signature 'ModelAnalytic'
convertPKModelAnalyticToPKModelODE(object)
```

```
## S4 method for signature 'ModelAnalyticSteadyState'
convertPKModelAnalyticToPKModelODE(object)
```

```
## S4 method for signature 'ModelAnalyticInfusion'
convertPKModelAnalyticToPKModelODE(object)
```

Arguments

object An object from the class Model.

Value

A ode model.

dataForArmEvaluation	<i>dataForArmEvaluation</i>
----------------------	-----------------------------

Description

dataForArmEvaluation

Usage

```
dataForArmEvaluation(object, arm, model)
```

```
## S4 method for signature 'Design'
dataForArmEvaluation(object, arm, model)
```

Arguments

object	An object Design from the class Design .
arm	...
model	An object Model from the class Model .

Value

A list containing data for arm evaluation in the design.

defineModel	<i>Define a model.</i>
-------------	------------------------

Description

Define a model.

Usage

```
defineModel(object, designs)
```

```
## S4 method for signature 'Model'
defineModel(object, designs)
```

Arguments

object	An object from the class Model .
designs	A list of objects from the class Design .

Value

A model defined either from the library of models or user defined.

```
defineModelEquationsFromStringToFunction  
    defineModelEquationsFromStringToFunction
```

Description

defineModelEquationsFromStringToFunction

Usage

```
defineModelEquationsFromStringToFunction(  
    object,  
    parametersNames,  
    outcomesWithAdministration,  
    outcomesWithNoAdministration  
)  
  
## S4 method for signature 'ModelAnalytic'  
defineModelEquationsFromStringToFunction(  
    object,  
    parametersNames,  
    outcomesWithAdministration,  
    outcomesWithNoAdministration  
)  
  
## S4 method for signature 'ModelAnalyticSteadyState'  
defineModelEquationsFromStringToFunction(  
    object,  
    parametersNames,  
    outcomesWithAdministration,  
    outcomesWithNoAdministration  
)  
  
## S4 method for signature 'ModelAnalyticInfusion'  
defineModelEquationsFromStringToFunction(  
    object,  
    parametersNames,  
    outcomesWithAdministration,  
    outcomesWithNoAdministration  
)  
  
## S4 method for signature 'ModelAnalyticInfusionSteadyState'  
defineModelEquationsFromStringToFunction(  
    object,  
    parametersNames,  
    outcomesWithAdministration,  
    outcomesWithNoAdministration  
)
```

```

    object,
    parametersNames,
    outcomesWithAdministration,
    outcomesWithNoAdministration
)

## S4 method for signature 'ModelODEBolus'
defineModelEquationsFromStringToFunction(
  object,
  parametersNames,
  outcomesWithAdministration,
  outcomesWithNoAdministration
)

## S4 method for signature 'ModelODEDoseInEquations'
defineModelEquationsFromStringToFunction(
  object,
  parametersNames,
  outcomesWithAdministration,
  outcomesWithNoAdministration
)

## S4 method for signature 'ModelODEDoseNotInEquations'
defineModelEquationsFromStringToFunction(
  object,
  parametersNames,
  outcomesWithAdministration,
  outcomesWithNoAdministration
)

## S4 method for signature 'ModelODEInfusionDoseInEquations'
defineModelEquationsFromStringToFunction(
  object,
  parametersNames,
  outcomesWithAdministration,
  outcomesWithNoAdministration
)

```

Arguments

object An object from the class [Model](#).
parametersNames Vector of parameter names.
outcomesWithAdministration Vector of the name of the outcome with administration.
outcomesWithNoAdministration Vector of the name of the outcome with no administration.

Value

....

```
defineModelFromLibraryOfModels
    Define a model from the library of models.
```

Description

Define a model from the library of models.

Usage

```
defineModelFromLibraryOfModels(object, designs)

## S4 method for signature 'Model'
defineModelFromLibraryOfModels(object, designs)
```

Arguments

object	An object from the class Model .
designs	A list of objects from the class Design .

Value

A model defined from the library of models.

```
defineModelType    Define the type of a model.
```

Description

Define the type of a model.

Usage

```
defineModelType(object, designs)

## S4 method for signature 'Model'
defineModelType(object, designs)
```

Arguments

object	An object from the class Model .
designs	A list of objects from the class Design .

Value

Return a model defined as analytic, ode, etc.

```
defineModelUserDefined
```

Define a user defined model.

Description

Define a user defined model.

Usage

```
defineModelUserDefined(object, designs)

## S4 method for signature 'Model'
defineModelUserDefined(object, designs)
```

Arguments

object	An object from the class Model .
designs	A list of objects from the class Design .

Value

A model giving a user defined model.

```
definePKModel
```

Define a PK model.

Description

Define a PK model.

Usage

```
definePKModel(object, outcomes)

## S4 method for signature 'ModelAnalytic'
definePKModel(object, outcomes)

## S4 method for signature 'ModelAnalyticSteadyState'
definePKModel(object, outcomes)

## S4 method for signature 'ModelAnalyticInfusion'
```

```

definePKModel(object, outcomes)

## S4 method for signature 'ModelODEDoseInEquations'
definePKModel(object, outcomes)

## S4 method for signature 'ModelODE'
definePKModel(object, outcomes)

## S4 method for signature 'ModelODEInfusionDoseInEquations'
definePKModel(object, outcomes)

```

Arguments

object An object from the class [Model](#).

outcomes A list giving the outcomes of the PK model.

Value

A model giving a PK model.

definePKPDMModel	<i>Define a PKPD model.</i>
------------------	-----------------------------

Description

Define a PKPD model.

Usage

```

definePKPDMModel(PKModel, PDModel, outcomes)

## S4 method for signature 'ModelAnalytic,ModelAnalytic'
definePKPDMModel(PKModel, PDModel, outcomes)

## S4 method for signature 'ModelAnalytic,ModelODE'
definePKPDMModel(PKModel, PDModel, outcomes)

## S4 method for signature 'ModelAnalyticSteadyState,ModelAnalyticSteadyState'
definePKPDMModel(PKModel, PDModel, outcomes)

## S4 method for signature 'ModelAnalyticSteadyState,ModelODE'
definePKPDMModel(PKModel, PDModel, outcomes)

## S4 method for signature 'ModelAnalyticInfusion,ModelAnalytic'
definePKPDMModel(PKModel, PDModel, outcomes)

## S4 method for signature 'ModelAnalyticInfusion,ModelODE'

```



```

definePKPDMModel(PKModel, PDModel, outcomes)

## S4 method for signature 'ModelODEBolus,ModelODE'
definePKPDMModel(PKModel, PDModel, outcomes)

## S4 method for signature 'ModelODEDoseInEquations,ModelODE'
definePKPDMModel(PKModel, PDModel, outcomes)

## S4 method for signature 'ModelODEDoseNotInEquations,ModelODE'
definePKPDMModel(PKModel, PDModel, outcomes)

## S4 method for signature 'ModelODEInfusion,ModelODE'
definePKPDMModel(PKModel, PDModel, outcomes)

## S4 method for signature 'ModelODEInfusionDoseInEquations,ModelODE'
definePKPDMModel(PKModel, PDModel, outcomes)

```

Arguments

PKModel An object from the class [Model](#).

PDModel An object from the class [Model](#).

outcomes A list giving the outcomes of the PKPD model.

Value

A model giving a PKPD model.

Design-class	<i>Class "Design"</i>
--------------	-----------------------

Description

The class Design defines information concerning the parametrization of the designs.

Objects from the class

Objects from the class Design can be created by calls of the form `Design(...)` where (...) are the parameters for the Design objects.

Slots for the Design objects

name: A string giving the name of the design.

size: An integer giving the number of subjects in the design.

arms: A list of the arms.

outcomesEvaluation: A list of the results of the design evaluation for the outcomes.

outcomesGradient: A list of the results of the design evaluation for the sensitivity indices.

numberOfArms: A numeric giving the number of arms in the design.

fim: An object of the class Fim containing the Fisher Information Matrix of the design.

Distribution-class *Class "Distribution"*

Description

The class defines all the required methods for a distribution object.

Objects from the class

Objects from the class Distribution can be created by calls of the form Distribution(...) where (...) are the parameters for the Distribution objects.

Slots for Distribution objects

parameters: A list containing the distribution parameters.

EvaluateArm *EvaluateArm*

Description

Evaluate an arm.

Usage

```
EvaluateArm(object, model, dataForModelEvaluation, fim)
```

```
## S4 method for signature 'Arm'
```

```
EvaluateArm(object, model, dataForModelEvaluation, fim)
```

Arguments

object	An object arm from the class Arm .
model	An object model from the class Model .
dataForModelEvaluation	

fim	An object fim from the class Fim .

Value

The object fim containing the Fisher Information Matrix the two lists evaluationOutcomes, outcomesGradient containing the results of the evaluation of the outcome and the sensitivity indices.

EvaluateDesign	<i>EvaluateDesign</i>
----------------	-----------------------

Description

Evaluate an design

Usage

```
EvaluateDesign(object, model, fim)
```

```
## S4 method for signature 'Design'
EvaluateDesign(object, model, fim)
```

Arguments

object	An object Design from the class Design .
model	An object model from the class Model .
fim	An object fim from the class Fim .

Value

The object Design with its slot fim, evaluationOutcomes, outcomesGradient updated.

EvaluateErrorModelDerivatives	<i>Evaluate the error model derivatives.</i>
-------------------------------	--

Description

Evaluate the error model derivatives.

Usage

```
EvaluateErrorModelDerivatives(object, evaluationOutcome)
```

```
## S4 method for signature 'ModelError'
EvaluateErrorModelDerivatives(object, evaluationOutcome)
```

Arguments

object	An object from the class ModelError .
evaluationOutcome	A list giving the results of the model evaluation.

Value

A list giving the error variance and the Sigma derivatives.

EvaluateFisherMatrix *Evaluate the Fisher matrix (population, individual and Bayesian)*

Description

Evaluate the Fisher matrix (population, individual and Bayesian)

Usage

```
EvaluateFisherMatrix(object, model, arm, modelEvaluation, modelVariance)
```

```
## S4 method for signature 'BayesianFim'
```

```
EvaluateFisherMatrix(object, model, arm, modelEvaluation, modelVariance)
```

```
## S4 method for signature 'IndividualFim'
```

```
EvaluateFisherMatrix(object, model, arm, modelEvaluation, modelVariance)
```

```
## S4 method for signature 'PopulationFim'
```

```
EvaluateFisherMatrix(object, model, arm, modelEvaluation, modelVariance)
```

Arguments

object	An object from the class Fim .
model	An object from the class Model .
arm	An object from the class Arm .
modelEvaluation	A list containing the evaluation results.
modelVariance	A list containing the model variance.

Value

An object from the class [Fim](#) containing the Fisher matrix.

EvaluateModel	<i>Evaluate a model.</i>
---------------	--------------------------

Description

Evaluate a model.

Usage

```
EvaluateModel(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelAnalytic'
EvaluateModel(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelAnalyticSteadyState'
EvaluateModel(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelAnalyticInfusion'
EvaluateModel(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelAnalyticInfusionSteadyState'
EvaluateModel(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelODEBolus'
EvaluateModel(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelODEDoseInEquations'
EvaluateModel(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelODEDoseNotInEquations'
EvaluateModel(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelODEInfusionDoseInEquations'
EvaluateModel(object, dataForModelEvaluation, arm)
```

Arguments

object	An object from the class Model .
dataForModelEvaluation	...
arm	An object from the class Arm .

Value

A list giving the results of the model evaluation.

EvaluateModelGradient *Evaluate model gradient.*

Description

Evaluate model gradient.

Usage

```
EvaluateModelGradient(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelAnalytic'
EvaluateModelGradient(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelAnalyticSteadyState'
EvaluateModelGradient(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelAnalyticInfusion'
EvaluateModelGradient(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelAnalyticInfusionSteadyState'
EvaluateModelGradient(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelODEBolus'
EvaluateModelGradient(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelODEDoseInEquations'
EvaluateModelGradient(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelODEDoseNotInEquations'
EvaluateModelGradient(object, dataForModelEvaluation, arm)

## S4 method for signature 'ModelODEInfusionDoseInEquations'
EvaluateModelGradient(object, dataForModelEvaluation, arm)
```

Arguments

object	An object from the class Model .
dataForModelEvaluation	
	...
arm	An object from the class Arm .

Value

A list giving the results of the model evaluation.

EvaluateVarianceFIM *Evaluate the variance of the Fisher information matrix.*

Description

Evaluate the variance of the Fisher information matrix.

Usage

```
EvaluateVarianceFIM(object, model, arm, modelEvaluation, modelVariance)
```

```
## S4 method for signature 'IndividualFim'
```

```
EvaluateVarianceFIM(object, model, arm, modelEvaluation, modelVariance)
```

```
## S4 method for signature 'PopulationFim'
```

```
EvaluateVarianceFIM(object, model, arm, modelEvaluation, modelVariance)
```

Arguments

object	An object from the class Fim .
model	An object from the class Model .
arm	An object from the class Arm .
modelEvaluation	A list containing the evaluation results.
modelVariance	A list containing the model variance.

Value

A list containing the matrices of the variance of the FIM.

EvaluateVarianceModel *Evaluate the variance of a model.*

Description

Evaluate the variance of a model.

Usage

```
EvaluateVarianceModel(object, arm, evaluationModel, data)
```

```
## S4 method for signature 'Model'
```

```
EvaluateVarianceModel(object, arm, evaluationModel, data)
```

Arguments

object	An object from the class Model .
arm	An object from the class Arm .
evaluationModel	A list giving the outputs of the model evaluation.
data	...

Value

Return a list giving the results of the evaluation of the model variance.

Evaluation-class	<i>Class "Evaluation"</i>
------------------	---------------------------

Description

A class storing information concerning the evaluation of a design.

Objects from the class

Objects from the class `Evaluation` can be created by calls of the form `Evaluation(...)` where (...) are the parameters for the `Evaluation` objects.

Slots for the Evaluation objects

name: A string giving the name of the project.

model: A object of class [Model](#) giving the model.

modelEquations: A list giving the model equations.

modelParameters: A list giving the model parameters.

modelError: A list giving the model error for each outcome of the model.

outcomes: A list giving the model outcomes.

designs: A list giving the designs to be evaluated.

fim: An object of the class `Fim` containing the Fisher Information Matrix of the design.

odeSolverParameters:

 FedorovWynnAlgorithm-class

Class "FedorovWynnAlgorithm"

Description

Class FedorovWynnAlgorithm represents an initial variable for ODE model.

Objects from the class FedorovWynnAlgorithm

Objects from the class FedorovWynnAlgorithm can be created by calls of the form `FedorovWynnAlgorithm(...)` where (...) are the parameters for the FedorovWynnAlgorithm objects.

Slots for FedorovWynnAlgorithm objects

elementaryProtocols: A list of vector for the initial elementary protocols.

numberOfSubjects: A vector for the number of subjects.

proportionsOfSubjects: A vector for the number of subjects.

OptimalDesign: A object Design giving the optimal Design.

showProcess: A boolean to show the process or not.

FisherMatrix: A vector giving the Fisher Information

optimalFrequencies: A vector of the optimal frequencies.

optimalSamplingTimes: A list of vectors for the optimal sampling times.

optimalDoses: A vector for the optimal doses.

 FedorovWynnAlgorithm_Rcpp

Fedorov-Wynn algorithm in Rcpp.

Description

Run the FedorovWynnAlgorithm in Rcpp

Usage

```
FedorovWynnAlgorithm_Rcpp(
  protocols_input,
  ndimen_input,
  nbprot_input,
  numprot_input,
  freq_input,
  nbdata_input,
  vectps_input,
```

```

    fisher_input,
    nok_input,
    protdep_input,
    freqdep_input
  )

```

Arguments

```

protocols_input      parameter protocols_input
ndimen_input        parameter ndimen_input
nbprot_input        parameter nbprot_input
numprot_input       parameter numprot_input
freq_input          parameter freq_input
nbdata_input        parameter nbdata_input
vectps_input        parameter vectps_input
fisher_input        parameter fisher_input
nok_input           parameter nok_input
protdep_input       parameter protdep_input
freqdep_input       parameter freqdep_input

```

Value

A list giving the results of the outputs of the FedorovWynn algorithm.

Fim-class

Class "Fim"

Description

A class storing information regarding the Fisher matrix. Type of the Fisher information: population ("PopulationFIM"), individual ("IndividualFIM") or Bayesian ("BayesianFIM").

Objects from the class

Objects from the class Fim can be created by calls of the form `Fim(...)` where (...) are the parameters for the Fim objects.

Slots for Fim objects

fisherMatrix: A matrix giving the Fisher matrix.

fixedEffects: A matrix giving the fixed effects of the Fisher matrix.

varianceEffects: A matrix giving the variance effects of the Fisher matrix.

shrinkage: A vector giving the shrinkage value of the parameters.

fisher.simplex	<i>Compute the fisher.simplex</i>
----------------	-----------------------------------

Description

Compute the fisher.simplex

Usage

```
fisher.simplex(simplex, optimizationObject, outcomes)
```

Arguments

simplex	A list giving the parameters of the simplex.
optimizationObject	An object from the class Optimization .
outcomes	A vector giving the outcomes of the arms.

Value

A list giving the results of the optimization.

fun.amoeba	<i>function fun.amoeba</i>
------------	----------------------------

Description

function fun.amoeba

Usage

```
fun.amoeba(p, y, ftol, itmax, funk, outcomes, data, showProcess)
```

Arguments

p	input is a matrix p whose ndim+1 rows are ndim-dimensional vectors which are the vertices of the starting simplex.
y	vector whose components must be pre-initialized to the values of funk evaluated at the ndim+1 vertices (rows) of p.
ftol	the fractional convergence tolerance to be achieved in the function value.
itmax	maximal number of iterations.
funk	multidimensional function to be optimized.
outcomes	A vector giving the outcomes.
data	a fixed set of data.
showProcess	A boolean for showing the process or not.

Value

A list containing the components of the optimized simplex. 'getColumnAndParametersNames-FIMInLatex.

```
generateFimsFromConstraints
```

Generate the fim from the constraints

Description

Generate the fim from the constraints

Usage

```
generateFimsFromConstraints(object, fims)
```

```
## S4 method for signature 'Optimization'
generateFimsFromConstraints(object)
```

Arguments

object An object from the class [Optimization](#).

fims A list of object from the class [Fim](#).

Value

A list giving the arms with their fims.

```
generateReportEvaluation
```

Generate the report for the evaluation

Description

Generate the report for the evaluation

Usage

```
generateReportEvaluation(  
  object,  
  evaluationObject,  
  outputPath,  
  outputFile,  
  plotOptions  
)  
  
## S4 method for signature 'BayesianFim'  
generateReportEvaluation(  
  object,  
  evaluationObject,  
  outputPath,  
  outputFile,  
  plotOptions  
)  
  
## S4 method for signature 'IndividualFim'  
generateReportEvaluation(  
  object,  
  evaluationObject,  
  outputPath,  
  outputFile,  
  plotOptions  
)  
  
## S4 method for signature 'PopulationFim'  
generateReportEvaluation(  
  object,  
  evaluationObject,  
  outputPath,  
  outputFile,  
  plotOptions  
)
```

Arguments

object	An object from the class Fim .
evaluationObject	A list giving the results of the evaluation of the model.
outputPath	A string giving the output path.
outputFile	A string giving the name of the output file.
plotOptions	A list giving the plot options.

Value

Return the report for the evaluation in html.

generateReportOptimization

Generate report for the optimization.

Description

Generate report for the optimization.

Usage

```
generateReportOptimization(  
  object,  
  optimizationObject,  
  outputPath,  
  outputFile,  
  plotOptions  
)  
  
## S4 method for signature 'FedorovWynnAlgorithm'  
generateReportOptimization(  
  object,  
  optimizationObject,  
  outputPath,  
  outputFile,  
  plotOptions  
)  
  
## S4 method for signature 'MultiplicativeAlgorithm'  
generateReportOptimization(  
  object,  
  optimizationObject,  
  outputPath,  
  outputFile,  
  plotOptions  
)  
  
## S4 method for signature 'PGBAlgorithm'  
generateReportOptimization(  
  object,  
  optimizationObject,  
  outputPath,  
  outputFile,  
  plotOptions  
)  
  
## S4 method for signature 'PSOAlgorithm'  
generateReportOptimization(  
  object,  
  optimizationObject,  
  outputPath,  
  outputFile,  
  plotOptions  
)
```

```

    object,
    optimizationObject,
    outputPath,
    outputFile,
    plotOptions
)

## S4 method for signature 'SimplexAlgorithm'
generateReportOptimization(
  object,
  optimizationObject,
  outputPath,
  outputFile,
  plotOptions
)

```

Arguments

object An object from the class [OptimizationAlgorithm](#).

optimizationObject An object from the class [Optimization](#).

outputPath A string giving the output path.

outputFile A string giving the name of the output file.

plotOptions A list giving the plot options.

Value

The report for the optimization in html.

```

generateSamplingsFromSamplingConstraints
Generate samplings from sampling constraints

```

Description

Generate samplings from sampling constraints

Usage

```

generateSamplingsFromSamplingConstraints(object)

## S4 method for signature 'SamplingTimeConstraints'
generateSamplingsFromSamplingConstraints(object)

```

Arguments

object An object from the class [SamplingTimeConstraints](#).

Value

A list of sampling times generated from the sampling constraints.

generateTables	<i>Generate the tables for the report.</i>
----------------	--

Description

Generate the tables for the report.

Usage

```
generateTables(object, plotOptions)

## S4 method for signature 'Evaluation'
generateTables(object, plotOptions)

## S4 method for signature 'Optimization'
generateTables(object, plotOptions)
```

Arguments

object	An object from the class PFIMProject .
plotOptions	A list giving the plot options.

Value

A list giving the kable able for the report (evaluation and optimization).

getAdjustedGradient	<i>getAdjustedGradient</i>
---------------------	----------------------------

Description

Get the adjusted gradient.

Usage

```
getAdjustedGradient(object, outcomesGradient)

## S4 method for signature 'LogNormal'
getAdjustedGradient(object, outcomesGradient)

## S4 method for signature 'Normal'
getAdjustedGradient(object, outcomesGradient)
```


Arguments

object An object distribution from the class [Distribution](#).
 outcomesGradient A list containing the evaluation of the outcome gradients.

Value

A list giving the adjusted gradient.

getAdministration *getAdministration*

Description

Get the administrations by outcome.

Usage

```
getAdministration(object, outcome)

## S4 method for signature 'Arm'
getAdministration(object, outcome)
```

Arguments

object An object Arm from the class [Arm](#).
 outcome A string giving the name of the outcome.

Value

The element of the list administrations containing the administration of the outcome outcome

getAdministrationConstraint *getAdministrationConstraint*

Description

Get the administration constraints by outcome.

Usage

```
getAdministrationConstraint(object, outcome)

## S4 method for signature 'Arm'
getAdministrationConstraint(object, outcome)
```

Arguments

object An object Arm from the class [Arm](#).
 outcome A string giving the name of the outcome.

Value

The element of the list `getAdministrationConstraint` containing the administration constraints of the outcome `outcome`

`getAdministrations` *getAdministrations*

Description

Get all the administration for an arm.

Usage

```
getAdministrations(object)

## S4 method for signature 'Arm'
getAdministrations(object)
```

Arguments

object An object Arm from the class [Arm](#).

Value

A list administrations of objects from the class `Administration` class giving the parameters of the administration for the object `Arm`.

`getAdministrationsConstraints`
 getAdministrationsConstraints

Description

Get the administrations constraints.

Usage

```
getAdministrationsConstraints(object)

## S4 method for signature 'Arm'
getAdministrationsConstraints(object)
```

Arguments

object An object Arm from the class [Arm](#).

Value

The list administrationsConstraints.

getArms *Get the arms of an object.*

Description

Get the arms of an object.

Usage

```
getArms(object)
```

```
## S4 method for signature 'Design'  
getArms(object)
```

```
## S4 method for signature 'OptimizationAlgorithm'  
getArms(object)
```

Arguments

object An object defined form a class of PFIM.

Value

A list containing the arms of the object.

getError *Get the parameter c.*

Description

Get the parameter c.

Usage

```
getError(object)
```

```
## S4 method for signature 'ModelError'  
getError(object)
```

Arguments

object An object from the class [ModelError](#).

Value

A numeric giving the parameter c.

getColumnAndParametersNamesFIM

Get the names of the names of the parameters associated to each column of the fim.

Description

Get the names of the names of the parameters associated to each column of the fim.

Usage

```
getColumnAndParametersNamesFIM(object, model)
```

```
## S4 method for signature 'BayesianFim'
getColumnAndParametersNamesFIM(object, model)
```

```
## S4 method for signature 'IndividualFim'
getColumnAndParametersNamesFIM(object, model)
```

```
## S4 method for signature 'PopulationFim'
getColumnAndParametersNamesFIM(object, model)
```

Arguments

object An object from the class [Fim](#).

model An object from the class [Model](#).

Value

A list giving the names of the parameters associated to each column of the fim.

```
getColumnAndParametersNamesFIMInLatex
```

Get the names of the names of the parameters associated to each column of the fim in Latex format.

Description

Get the names of the names of the parameters associated to each column of the fim in Latex format.

Usage

```
getColumnAndParametersNamesFIMInLatex(object, model)
```

```
## S4 method for signature 'BayesianFim'
getColumnAndParametersNamesFIMInLatex(object, model)
```

```
## S4 method for signature 'IndividualFim'
getColumnAndParametersNamesFIMInLatex(object, model)
```

```
## S4 method for signature 'PopulationFim'
getColumnAndParametersNamesFIMInLatex(object, model)
```

Arguments

object	An object from the class Fim .
model	An object from the class Model .

Value

A list giving the names of the parameters associated to each column of the fim in Latex format.

```
getConditionNumberFixedEffects
```

Get the condition number of the matrix of the fixed effects.

Description

Get the condition number of the matrix of the fixed effects.

Usage

```
getConditionNumberFixedEffects(object)
```

```
## S4 method for signature 'Fim'
getConditionNumberFixedEffects(object)
```

Arguments

object An object from the class [Fim](#).

Value

A numeric giving the condition number of the matrix of the fixed effects.

getConditionNumberVarianceEffects

Get the condition number of the matrix of the variance effects.

Description

Get the condition number of the matrix of the variance effects.

Usage

```
getConditionNumberVarianceEffects(object)
```

```
## S4 method for signature 'Fim'  
getConditionNumberVarianceEffects(object)
```

```
## S4 method for signature 'BayesianFim'  
getConditionNumberVarianceEffects(object)
```

Arguments

object An object from the class [Fim](#)..

Value

A numeric giving the condition number of the matrix of the variance effects.

getContent

Get content of a library of models.

Description

Get content of a library of models.

Usage

```
getContent(object)
```

```
## S4 method for signature 'LibraryOfModels'  
getContent(object)
```

Arguments

object An object from the class [LibraryOfModels](#).

Value

A list giving the content of the library of models.

`getCorrelationMatrix` *Get the correlation matrix.*

Description

Get the correlation matrix.

Usage

```
getCorrelationMatrix(object)

## S4 method for signature 'Fim'
getCorrelationMatrix(object)

## S4 method for signature 'Evaluation'
getCorrelationMatrix(object)

## S4 method for signature 'Optimization'
getCorrelationMatrix(object)
```

Arguments

object An object from the class [Fim](#).

Value

The correlation matrix of the fim.

`getDataForArmEvaluation`
getDataForArmEvaluation

Description

`getDataForArmEvaluation`

Usage

```
getDataForArmEvaluation(object)

## S4 method for signature 'Arm'
getDataForArmEvaluation(object)
```

Arguments

object An object Arm from the class [Arm](#).

Value

A list containing the data for arm evaluation.

getDataFrameResults *Get the dataframe of the results.*

Description

Get the dataframe of the results.

Usage

```
getDataFrameResults(object)

## S4 method for signature 'FedorovWynnAlgorithm'
getDataFrameResults(object)

## S4 method for signature 'MultiplicativeAlgorithm'
getDataFrameResults(object)

## S4 method for signature 'Optimization'
getDataFrameResults(object)
```

Arguments

object An object from the class [OptimizationAlgorithm](#).

Value

Return the dataframe of the results.

getDcriterion	<i>Get the D criterion of the fim.</i>
---------------	--

Description

Get the D criterion of the fim.

Usage

```
getDcriterion(object)

## S4 method for signature 'Fim'
getDcriterion(object)

## S4 method for signature 'Evaluation'
getDcriterion(object)

## S4 method for signature 'Optimization'
getDcriterion(object)
```

Arguments

object An object from the class [Fim](#).

Value

A numeric giving the D criterion of the fim.

getDelta	<i>Get the parameter delta</i>
----------	--------------------------------

Description

Get the parameter delta

Usage

```
getDelta(object)

## S4 method for signature 'MultiplicativeAlgorithm'
getDelta(object)
```

Arguments

object An object from the class [MultiplicativeAlgorithm](#).

Value

A numeric giving the parameter delta.

getDerivatives	<i>Get the derivatives of the model error equation.</i>
----------------	---

Description

Get the derivatives of the model error equation.

Usage

```
getDerivatives(object)

## S4 method for signature 'ModelError'
getDerivatives(object)
```

Arguments

object An object from the class [ModelError](#).

Value

The derivatives of the model error equation.

getDescription	<i>Get the description of a model.</i>
----------------	--

Description

Get the description of a model.

Usage

```
getDescription(object)

## S4 method for signature 'Model'
getDescription(object)
```

Arguments

object An object from the class [Model](#).

Value

A list giving the description of a model.

getDesigns	<i>Get the designs.</i>
------------	-------------------------

Description

Get the designs.

Usage

```
getDesigns(object)
```

```
## S4 method for signature 'PFIMProject'  
getDesigns(object)
```

Arguments

object An object from the class [PFIMProject](#).

Value

A list giving the designs of the object.

getDeterminant	<i>Get the determinant of the fim.</i>
----------------	--

Description

Get the determinant of the fim.

Usage

```
getDeterminant(object)
```

```
## S4 method for signature 'Fim'  
getDeterminant(object)
```

```
## S4 method for signature 'Evaluation'  
getDeterminant(object)
```

```
## S4 method for signature 'Optimization'  
getDeterminant(object)
```

Arguments

object An object from the class [Fim](#).

Value

A numeric giving the determinant of the fim.

getDistribution	<i>Get the distribution.</i>
-----------------	------------------------------

Description

Get the distribution.

Usage

```
getDistribution(object)
```

```
## S4 method for signature 'ModelParameter'  
getDistribution(object)
```

Arguments

object An object from the class [ModelParameter](#).

Value

The parameter distribution.

getDose	<i>getDose</i>
---------	----------------

Description

Get the amount of doses.

Usage

```
getDose(object)
```

```
## S4 method for signature 'Administration'  
getDose(object)
```

```
## S4 method for signature 'AdministrationConstraints'  
getDose(object)
```

Arguments

object An object Administration from the class [Administration](#).

Value

The numeric amount_dose giving the amount of doses.

getEigenValues	<i>Get the eigenvalues of the fim.</i>
----------------	--

Description

Get the eigenvalues of the fim.

Usage

```
getEigenValues(object)

## S4 method for signature 'Fim'
getEigenValues(object)
```

Arguments

object An object from the class [Fim](#).

Value

A vector giving the eigenvalues of the fim.

getElementaryProtocols	<i>Get the elementary protocols.</i>
------------------------	--------------------------------------

Description

Get the elementary protocols.

Usage

```
getElementaryProtocols(object, fims)

## S4 method for signature 'Optimization'
getElementaryProtocols(object, fims)
```

Arguments

object An object from the class [Optimization](#).
fims A list of object from the class [Fim](#).

Value

A list containing the results of the evaluation of the elementary protocols giving the numberOfTimes, nbOfDimensions, totalCost, samplingTimes and the fisherMatrices

getEquation	<i>Get the equation of a model error.</i>
-------------	---

Description

Get the equation of a model error.

Usage

```
getEquation(object)
```

```
## S4 method for signature 'ModelError'
getEquation(object)
```

Arguments

object An object from the class [ModelError](#).

Value

An expression giving the equation of a model error.

getEquations	<i>Get the equations of a model.</i>
--------------	--------------------------------------

Description

Get the equations of a model.

Usage

```
getEquations(object)
```

```
## S4 method for signature 'Model'
getEquations(object)
```

Arguments

object An object from the class [Model](#).

Value

The list giving the equations of the model.

```
getEquationsAfterInfusion  
    Get the equations after infusion.
```

Description

Get the equations after infusion.

Usage

```
getEquationsAfterInfusion(object)  
  
## S4 method for signature 'Model'  
getEquationsAfterInfusion(object)
```

Arguments

object An object from the class [Model](#).

Value

A list giving the equations after the infusion.

```
getEquationsDuringInfusion  
    Get the equations during infusion.
```

Description

Get the equations during infusion.

Usage

```
getEquationsDuringInfusion(object)  
  
## S4 method for signature 'Model'  
getEquationsDuringInfusion(object)
```

Arguments

object An object from the class [Model](#).

Value

A list giving the equations during the infusion.

getEvaluationFIMResults

Get the results of the evaluation.

Description

Get the results of the evaluation.

Usage

```
getEvaluationFIMResults(object)
```

```
## S4 method for signature 'Optimization'  
getEvaluationFIMResults(object)
```

Arguments

object An object from the class [Optimization](#).

Value

An object from the class [Evaluation](#) giving the evaluation results for the optimal design.

getEvaluationInitialDesignResults

Get the evaluation results of the initial design.

Description

Get the evaluation results of the initial design.

Usage

```
getEvaluationInitialDesignResults(object)
```

```
## S4 method for signature 'Optimization'  
getEvaluationInitialDesignResults(object)
```

Arguments

object An object from the class [Optimization](#).

Value

The object from the class [Evaluation](#) giving the results of the evaluation of the initial design.

getFim	<i>getFim</i>
--------	---------------

Description

Get the fim of an of an object.

Usage

```
getFim(object)
```

```
## S4 method for signature 'Design'
getFim(object)
```

```
## S4 method for signature 'PFIMProject'
getFim(object)
```

```
## S4 method for signature 'OptimizationAlgorithm'
getFim(object)
```

Arguments

object An object defined form a class of PFIM.

Value

The FIM of the object.

getFisherMatrix	<i>Get the FIM.</i>
-----------------	---------------------

Description

Get the FIM.

Usage

```
getFisherMatrix(object)
```

```
## S4 method for signature 'Fim'
getFisherMatrix(object)
```

```
## S4 method for signature 'Evaluation'
getFisherMatrix(object)
```

```
## S4 method for signature 'Optimization'
getFisherMatrix(object)
```

Arguments

object An object from the class [Fim](#).

Value

A matrix giving the FIM.

getFixedEffects *Get the matrix of fixed effects.*

Description

Get the matrix of fixed effects.

Usage

```
getFixedEffects(object)

## S4 method for signature 'Fim'
getFixedEffects(object)
```

Arguments

object An object from the class [Fim](#).

Value

The matrix of the fixed effects.

getFixedMu *Get the fixed effect.*

Description

Get the fixed effect.

Usage

```
getFixedMu(object)

## S4 method for signature 'ModelParameter'
getFixedMu(object)
```

Arguments

object An object from the class [ModelParameter](#).

Value

A boolean giving the fixed mu.

`getFixedOmega` *Get the fixed variance.*

Description

Get the fixed variance.

Usage

```
getFixedOmega(object)
```

```
## S4 method for signature 'ModelParameter'  
getFixedOmega(object)
```

Arguments

`object` An object from the class [ModelParameter](#).

Value

A boolean giving the fixed omega.

`getFixedParameters` *Get the fixed parameters.*

Description

Get the fixed parameters.

Usage

```
getFixedParameters(object)
```

```
## S4 method for signature 'Model'  
getFixedParameters(object)
```

Arguments

`object` An object from the class [Model](#).

Value

A list giving the fixed parameters of the model.

<code>getFixedTimes</code>	<i>Get the fixed sampling times.</i>
----------------------------	--------------------------------------

Description

Get the fixed sampling times.

Usage

```
getFixedTimes(object)
```

```
## S4 method for signature 'SamplingTimeConstraints'  
getFixedTimes(object)
```

Arguments

`object` An object from the class [SamplingTimeConstraints](#).

Value

A vector giving the fixed sampling times.

<code>getInitialConditions</code>	<i>getInitialConditions</i>
-----------------------------------	-----------------------------

Description

Get the initial condition for the evaluation of an ode model.

Usage

```
getInitialConditions(object)
```

```
## S4 method for signature 'Arm'  
getInitialConditions(object)
```

```
## S4 method for signature 'Model'  
getInitialConditions(object)
```

Arguments

`object` An object `Arm` from the class [Arm](#).

Value

The list `initialConditions` for the object `Arm`.

```
getIterationAndCriteria
```

Get the iteration with the convergence criteria.

Description

Get the iteration with the convergence criteria.

Usage

```
getIterationAndCriteria(object)
```

S4 method for signature 'OptimizationAlgorithm'
getIterationAndCriteria(object)

Arguments

object An object from the class [OptimizationAlgorithm](#).

Value

A dataframe giving the iteration with the convergence criteria.

```
getLambda
```

Get the parameter lambda.

Description

Get the parameter lambda.

Usage

```
getLambda(object)
```

S4 method for signature 'MultiplicativeAlgorithm'
getLambda(object)

Arguments

object An object from the class [MultiplicativeAlgorithm](#).

Value

A numeric giving the parameter lambda.

getLibraryPDMODELS *Get the library of PD models.*

Description

Get the library of PD models.

Usage

```
getLibraryPDMODELS(object)

## S4 method for signature 'LibraryOfModels'
getLibraryPDMODELS(object)
```

Arguments

object An object from the class [LibraryOfModels](#).

Value

A list giving the PD models.

getLibraryPKMODELS *Get the library of PK models.*

Description

Get the library of PK models.

Usage

```
getLibraryPKMODELS(object)

## S4 method for signature 'LibraryOfModels'
getLibraryPKMODELS(object)
```

Arguments

object An object from the class [LibraryOfModels](#).

Value

A list giving the PK models.

getMinSampling	<i>Get the minimal sampling times.</i>
----------------	--

Description

Get the minimal sampling times.

Usage

```
getMinSampling(object)
```

```
## S4 method for signature 'SamplingTimeConstraints'  
getMinSampling(object)
```

Arguments

object An object from the class [SamplingTimeConstraints](#).

Value

A numeric giving the minimal sampling times.

getModel	<i>Get the model.</i>
----------	-----------------------

Description

Get the model.

Usage

```
getModel(object)
```

```
## S4 method for signature 'PFIMProject'  
getModel(object)
```

Arguments

object An object from the class [PFIMProject](#).

Value

The model of the object.

getModelEquations *Get the model equations.*

Description

Get the model equations.

Usage

```
getModelEquations(object)

## S4 method for signature 'PFIMProject'
getModelEquations(object)
```

Arguments

object An object from the class [PFIMProject](#).

Value

A list giving the model equations.

getModelError *Get the model error.*

Description

Get the model error.

Usage

```
getModelError(object)

## S4 method for signature 'Model'
getModelError(object)

## S4 method for signature 'PFIMProject'
getModelError(object)
```

Arguments

object An object defined form a class of PFIM.

Value

The model error of the object.

getModelErrorParametersValues
Get the values of the model error parameters.

Description

Get the values of the model error parameters.

Usage

```
getModelErrorParametersValues(object)
```

```
## S4 method for signature 'Model'  
getModelErrorParametersValues(object)
```

Arguments

object An object from the class [Model](#).

Value

A list giving the values of the model error parameters.

getModelFromLibrary *Get a model from the library of models.*

Description

Get a model from the library of models.

Usage

```
getModelFromLibrary(object)
```

```
## S4 method for signature 'Model'  
getModelFromLibrary(object)
```

Arguments

object An object from the class [Model](#).

Value

Return a model from the the library of models.

getModelParameters *Get the model parameters.*

Description

Get the model parameters.

Usage

```
getModelParameters(object)  
  
## S4 method for signature 'PFIMProject'  
getModelParameters(object)
```

Arguments

object An object from the class [PFIMProject](#).

Value

A list giving the model parameters.

getModelParametersValues
 Get the values of the model parameters.

Description

Get the values of the model parameters.

Usage

```
getModelParametersValues(object)  
  
## S4 method for signature 'Model'  
getModelParametersValues(object)
```

Arguments

object An object from the class [Model](#).

Value

A list giving the values of the model parameters.

getMu	<i>getMu</i>
-------	--------------

Description

Get the fixed effect of an object.

Usage

```
getMu(object)

## S4 method for signature 'Distribution'
getMu(object)

## S4 method for signature 'ModelParameter'
getMu(object)
```

Arguments

object An object defined form a class of PFIM.

Value

The object with the updated fixed effect.

getName	<i>getName</i>
---------	----------------

Description

Get the name of an object

Usage

```
getName(object)

## S4 method for signature 'Arm'
getName(object)

## S4 method for signature 'Design'
getName(object)

## S4 method for signature 'ModelParameter'
getName(object)

## S4 method for signature 'LibraryOfModels'
```

```
getName(object)

## S4 method for signature 'Model'
getName(object)

## S4 method for signature 'PFIMProject'
getName(object)
```

Arguments

object An object defined form a class of PFIM.

Value

A character string name giving the name of the object.

getNames	<i>getNames</i>
----------	-----------------

Description

Get the names of an object.

Usage

```
getNames(object)

## S4 method for signature 'list'
getNames(object)
```

Arguments

object An object defined form a class of PFIM.

Value

A vector giving the names of the object.

getNumberOfArms	<i>getNumberOfArms</i>
-----------------	------------------------

Description

Get the number of arms in a design.

Usage

```
getNumberOfArms(object)

## S4 method for signature 'Design'
getNumberOfArms(object)
```

Arguments

object An object Design from the class [Design](#).

Value

A numeric numberOfArms giving the number of arms in the design.

getNumberOfIterations	<i>Get the number of iterations.</i>
-----------------------	--------------------------------------

Description

Get the number of iterations.

Usage

```
getNumberOfIterations(object)

## S4 method for signature 'MultiplicativeAlgorithm'
getNumberOfIterations(object)
```

Arguments

object An object from the class [MultiplicativeAlgorithm](#).

Value

A numeric giving the number of iterations.

getNumberOfParameters *Get the number of parameters.*

Description

Get the number of parameters.

Usage

```
getNumberOfParameters(object)
```

```
## S4 method for signature 'Model'  
getNumberOfParameters(object)
```

Arguments

object An object from the class [Model](#).

Value

A numeric giving the number of parameters of the model.

getNumberOfSamplingsOptimisable
Get the number of sampling times that are optimisable.

Description

Get the number of sampling times that are optimisable.

Usage

```
getNumberOfSamplingsOptimisable(object)
```

```
## S4 method for signature 'SamplingTimeConstraints'  
getNumberOfSamplingsOptimisable(object)
```

Arguments

object An object from the class [SamplingTimeConstraints](#).

Value

A vector giving the number of sampling times that are optimisable.

`getNumberOfTimesByWindows`*Get the number of sampling times by windows.*

Description

Get the number of sampling times by windows.

Usage

```
getNumberOfTimesByWindows(object)
```

```
## S4 method for signature 'SamplingTimeConstraints'  
getNumberOfTimesByWindows(object)
```

Arguments

`object` An object from the class [SamplingTimeConstraints](#).

Value

A vector giving the number of sampling times by windows.

`getOdeSolverParameters`*getOdeSolverParameters*

Description

Get the parameters for the ode solvers of an object.

Usage

```
getOdeSolverParameters(object)
```

```
## S4 method for signature 'Model'  
getOdeSolverParameters(object)
```

```
## S4 method for signature 'PFIMProject'  
getOdeSolverParameters(object)
```

Arguments

`object` An object defined form a class of PFIM.

Value

The list giving the parameters for the ode solvers.

getOmega	<i>Get the matrix omega of an object.</i>
----------	---

Description

Get the matrix omega of an object.

Usage

```
getOmega(object)

## S4 method for signature 'Distribution'
getOmega(object)

## S4 method for signature 'ModelParameter'
getOmega(object)
```

Arguments

object An object defined form a class of PFIM.

Value

The matrix omega of an object.

getOptimalDesign	<i>Get the optimal design.</i>
------------------	--------------------------------

Description

Get the optimal design.

Usage

```
getOptimalDesign(object)

## S4 method for signature 'OptimizationAlgorithm'
getOptimalDesign(object)
```

Arguments

object An object from the class [OptimizationAlgorithm](#).

Value

The optimal design.

`getOptimalFrequencies` *Get the optimal frequencies*

Description

Get the optimal frequencies

Usage

```
getOptimalFrequencies(object)
```

```
## S4 method for signature 'FedorovWynnAlgorithm'  
getOptimalFrequencies(object)
```

Arguments

`object` An object from the class [FedorovWynnAlgorithm](#).

Value

A vector giving the optimal frequencies

`getOptimalWeights` *Get the optimal weights.*

Description

Get the optimal weights.

Usage

```
getOptimalWeights(object)
```

```
## S4 method for signature 'MultiplicativeAlgorithm'  
getOptimalWeights(object)
```

Arguments

`object` An object from the class [MultiplicativeAlgorithm](#).

Value

A vector giving the optimal weights.

getOptimizationResults

Get the optimization results.

Description

Get the optimization results.

Usage

```
getOptimizationResults(object)
```

```
## S4 method for signature 'Optimization'  
getOptimizationResults(object)
```

Arguments

object An object from the class [Optimization](#).

Value

An object from the class [OptimizationAlgorithm](#) giving the optimization results.

getOptimizer

Get the optimization algorithm.

Description

Get the optimization algorithm.

Usage

```
getOptimizer(object)
```

```
## S4 method for signature 'PFIMProject'  
getOptimizer(object)
```

Arguments

object An object from the class [PFIMProject](#).

Value

A string giving the name of the optimization algorithm.

getOptimizerParameters
Get the optimization parameters.

Description

Get the optimization parameters.

Usage

```
getOptimizerParameters(object)  
  
## S4 method for signature 'PFIMProject'  
getOptimizerParameters(object)
```

Arguments

object An object from the class [PFIMProject](#).

Value

A list giving the optimization parameters.

getOutcome *getOutcome*

Description

Get the outcome of an object.

Usage

```
getOutcome(object)  
  
## S4 method for signature 'Administration'  
getOutcome(object)  
  
## S4 method for signature 'AdministrationConstraints'  
getOutcome(object)  
  
## S4 method for signature 'ModelError'  
getOutcome(object)  
  
## S4 method for signature 'SamplingTimeConstraints'  
getOutcome(object)  
  
## S4 method for signature 'SamplingTimes'  
getOutcome(object)
```

Arguments

object An object defined from a class of PFIM.

Value

A string giving the outcome of the object.

getOutcomes *Get the outcomes of a model.*

Description

Get the outcomes of a model.

Usage

```
getOutcomes(object)

## S4 method for signature 'Model'
getOutcomes(object)

## S4 method for signature 'PFIMProject'
getOutcomes(object)
```

Arguments

object An object from the class [Model](#).

Value

A list giving the outcomes of the model.

getOutcomesEvaluation *getOutcomesEvaluation*

Description

Get the results of the evaluation of the outcomes.

Usage

```
getOutcomesEvaluation(object)

## S4 method for signature 'Design'
getOutcomesEvaluation(object)
```

Arguments

object An object Design from the class [Design](#).

Value

The list outcomesEvaluation containing the results of the design evaluation for the outcomes.

getOutcomesForEvaluation *Get the outcomes of a model used for the evaluation (is scales outcomes).*

Description

Get the outcomes of a model used for the evaluation (is scales outcomes).

Usage

```
getOutcomesForEvaluation(object)  
  
## S4 method for signature 'Model'  
getOutcomesForEvaluation(object)
```

Arguments

object An object from the class [Model](#).

Value

A list giving the outcomes of a model used for the evaluation (is scales outcomes).

getOutcomesGradient *getOutcomesGradient*

Description

Get the results of the evaluation of the outcome gradients.

Usage

```
getOutcomesGradient(object)  
  
## S4 method for signature 'Design'  
getOutcomesGradient(object)
```

Arguments

object An object Design from the class [Design](#).

Value

The list outcomesGradient containing the results of the design evaluation for the outcome gradients.

getParameters *Get the parameters of an object.*

Description

Get the parameters of an object.

Usage

```
getParameters(object)

## S4 method for signature 'ModelError'
getParameters(object)

## S4 method for signature 'Distribution'
getParameters(object)

## S4 method for signature 'Model'
getParameters(object)
```

Arguments

object An object defined form a class of PFIM.

Value

Return the list of the parameters of the object.

getPDMModel	<i>Get a PD model.</i>
-------------	------------------------

Description

Get a PD model.

Usage

```
getPDMModel(object, PDModelName)
```

```
## S4 method for signature 'LibraryOfPKPDMModels'  
getPDMModel(object, PDModelName)
```

Arguments

object	An object from the class LibraryOfPKPDMModels .
PDModelName	A string giving the name of the PD model.

Value

Return a PD model.

getPKModel	<i>Get a PK model.</i>
------------	------------------------

Description

Get a PK model.

Usage

```
getPKModel(object, PKModelName)
```

```
## S4 method for signature 'LibraryOfPKPDMModels'  
getPKModel(object, PKModelName)
```

Arguments

object	An object from the class LibraryOfPKPDMModels .
PKModelName	A string giving the name of the PK model.

Value

Return a PK model.

getPKPDModel	<i>Get a PKPD model.</i>
--------------	--------------------------

Description

Get a PKPD model.

Usage

```
getPKPDModel(object, namesModel)
```

```
## S4 method for signature 'LibraryOfPKPDModels'  
getPKPDModel(object, namesModel)
```

Arguments

object	An object from the class LibraryOfPKPDModels .
namesModel	A vector of strings giving the names of the PK and PD models.

Value

Return a PKPD model.

getPlotOptions	<i>Get the plot options for graphs responses and SI</i>
----------------	---

Description

Get the plot options for graphs responses and SI

Usage

```
getPlotOptions(plotOptions, outcomesNames)
```

Arguments

plotOptions	A list giving the plots options.
outcomesNames	A list giving the output names.

Value

The list containing the plot options.

getProportionsOfSubjects
Get the proportion of subjects.

Description

Get the proportion of subjects.

Usage

```
getProportionsOfSubjects(object)

## S4 method for signature 'Optimization'
getProportionsOfSubjects(object)
```

Arguments

object An object from the class [Optimization](#).

Value

A vector giving the proportion of subjects.

getRSE *Get the RSE*

Description

Get the RSE

Usage

```
getRSE(object, model)

## S4 method for signature 'BayesianFim'
getRSE(object, model)

## S4 method for signature 'Evaluation'
getRSE(object, model)

## S4 method for signature 'IndividualFim'
getRSE(object, model)

## S4 method for signature 'Optimization'
getRSE(object, model)

## S4 method for signature 'PopulationFim'
getRSE(object, model)
```

Arguments

object An object from the class [Fim](#).
 model An object from the class [Model](#).

Value

A vector giving the RSE.

getSamplings *Get the sampling of an object.*

Description

Get the sampling of an object.

Usage

```
getSamplings(object)

## S4 method for signature 'SamplingTimeConstraints'
getSamplings(object)

## S4 method for signature 'SamplingTimes'
getSamplings(object)
```

Arguments

object An object defined form a class of PFIM.

Value

A list of the samplings of the object.

getSamplingsWindows *Get the windows for the sampling times.*

Description

Get the windows for the sampling times.

Usage

```
getSamplingsWindows(object)

## S4 method for signature 'SamplingTimeConstraints'
getSamplingsWindows(object)
```

Arguments

object An object from the class [SamplingTimeConstraints](#).

Value

A list giving the vector of the windows for the sampling times.

getSamplingTime *getSamplingTime*

Description

Get the sampling times by outcome.

Usage

```
getSamplingTime(object, outcome)

## S4 method for signature 'Arm'
getSamplingTime(object, outcome)
```

Arguments

object An object Arm from the class [Arm](#).
outcome A string giving the name of the outcome.

Value

The element of the list `samplingTimes` containing the sampling times of the outcome `outcome`

getSamplingTimeConstraint *getSamplingTimeConstraint*

Description

Get the sampling times constraints by outcome.

Usage

```
getSamplingTimeConstraint(object, outcome)

## S4 method for signature 'Arm'
getSamplingTimeConstraint(object, outcome)
```

Arguments

object An object Arm from the class [Arm](#).
 outcome A string giving the name of the outcome.

Value

The element of the list `samplingTimesConstraints` containing the sampling times constraints of the outcome `outcome`

`getSamplingTimes` *getSamplingTimes*

Description

Get the vectors of sampling times for an arm.

Usage

```
getSamplingTimes(object)

## S4 method for signature 'Arm'
getSamplingTimes(object)
```

Arguments

object An object Arm from the class [Arm](#).

Value

The list `samplingTimes` for the object Arm.

`getSamplingTimesConstraints`
 getSamplingTimesConstraints

Description

Get the sampling times constraints.

Usage

```
getSamplingTimesConstraints(object)

## S4 method for signature 'Arm'
getSamplingTimesConstraints(object)
```

Arguments

object An object Arm from the class [Arm](#).

Value

The list getSamplingTimesConstraints.

getSE *Get the SE.*

Description

Get the SE.

Usage

```
getSE(object)

## S4 method for signature 'Fim'
getSE(object)

## S4 method for signature 'Evaluation'
getSE(object)

## S4 method for signature 'Optimization'
getSE(object)
```

Arguments

object An object from the class [Fim](#).

Value

A vector giving the SE.

getShrinkage *Get the shrinkage.*

Description

Get the shrinkage.

Usage

```

getShrinkage(object)

## S4 method for signature 'BayesianFim'
getShrinkage(object)

## S4 method for signature 'Evaluation'
getShrinkage(object)

## S4 method for signature 'IndividualFim'
getShrinkage(object)

## S4 method for signature 'Optimization'
getShrinkage(object)

## S4 method for signature 'PopulationFim'
getShrinkage(object)

```

Arguments

object An object from the class [Fim](#).

Value

A vector giving the shrinkage of the Bayesian fim.

getSigmaInter	<i>Get the parameter sigma inter.</i>
---------------	---------------------------------------

Description

Get the parameter sigma inter.

Usage

```

getSigmaInter(object)

## S4 method for signature 'ModelError'
getSigmaInter(object)

```

Arguments

object An object from the class [ModelError](#).

Value

A numeric giving the parameter sigma inter.

getSigmaSlope	<i>Get the parameter sigma slope.</i>
---------------	---------------------------------------

Description

Get the parameter sigma slope.

Usage

```
getSigmaSlope(object)

## S4 method for signature 'ModelError'
getSigmaSlope(object)
```

Arguments

object An object from the class [ModelError](#).

Value

A numeric giving the parameter sigma slope.

getSize	<i>getSize</i>
---------	----------------

Description

Get the size of an object.

Usage

```
getSize(object)

## S4 method for signature 'Arm'
getSize(object)

## S4 method for signature 'Design'
getSize(object)
```

Arguments

object An object defined form a class of PFIM.

Value

A numeric giving the size of the object.

getTau	<i>getTau</i>
--------	---------------

Description

Get the frequency tau.

Usage

```
getTau(object)
```

```
## S4 method for signature 'Administration'  
getTau(object)
```

Arguments

object An object Administration from the class [Administration](#).

Value

The numeric tau giving the frequency tau.

getTimeDose	<i>getTimeDose</i>
-------------	--------------------

Description

Get the times vector when doses are given.

Usage

```
getTimeDose(object)
```

```
## S4 method for signature 'Administration'  
getTimeDose(object)
```

Arguments

object An object Administration from the class [Administration](#).

Value

The vector timeDose giving the times when the doses are given.

getTinf	<i>Get the infusion duration.</i>
---------	-----------------------------------

Description

Get the infusion duration.

Usage

```
getTinf(object)

## S4 method for signature 'Administration'
getTinf(object)
```

Arguments

object An object Administration from the class [Administration](#).

Value

The numeric Tinf giving the infusion duration Tinf.

getVariables	<i>Return the variable of an ode model</i>
--------------	--

Description

The class ModelODEBolus defines information concerning the construction of an ode model bolus. The class ModelODEBolus inherits from the class ModelBolus.

Usage

```
getVariables(object)

## S4 method for signature 'ModelODE'
getVariables(object)

## S4 method for signature 'ModelODEBolus'
getVariables(object)

## S4 method for signature 'ModelInfusion'
getVariables(object)
```

Arguments

object An object from the class [Model](#).

Value

Return the variable of an ode model

`getVarianceEffects` *Get the matrix of the variance effects.*

Description

Get the matrix of the variance effects.

Usage

```
getVarianceEffects(object)

## S4 method for signature 'Fim'
getVarianceEffects(object)
```

Arguments

`object` An object from the class [Fim](#).

Value

The matrix of the variance effects.

`getWeightThreshold` *Get the parameter weightThreshold*

Description

Get the parameter `weightThreshold`

Usage

```
getWeightThreshold(object)

## S4 method for signature 'MultiplicativeAlgorithm'
getWeightThreshold(object)
```

Arguments

`object` An object from the class [MultiplicativeAlgorithm](#).

Value

A numeric giving the `WeightThreshold`.

IndividualFim-class *Class "Fim"*

Description

A class storing information regarding the individual Fisher matrix. The class IndividualFim inherits from the class Fim.

initialize,Administration-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'Administration'
initialize(.Object, outcome, timeDose, dose, Tinf, tau)
```

Arguments

.Object	.Object
outcome	outcome
timeDose	timeDose
dose	dose
Tinf	Tinf
tau	tau

Value

Administration

```
initialize,AdministrationConstraints-method
      initialize
```

Description

initialize

Usage

```
## S4 method for signature 'AdministrationConstraints'
initialize(.Object, outcome, doses)
```

Arguments

.Object	.Object
outcome	outcome
doses	doses

```
initialize,Arm-method initialize
```

Description

initialize

Usage

```
## S4 method for signature 'Arm'
initialize(
  .Object,
  name,
  size,
  administrations,
  initialConditions,
  samplingTimes,
  administrationsConstraints,
  samplingTimesConstraints,
  dataForArmEvaluation
)
```

Arguments

.Object	.Object
name	name
size	size
administrations	administrations
initialConditions	initialConditions
samplingTimes	samplingTimes
administrationsConstraints	administrationsConstraints
samplingTimesConstraints	samplingTimesConstraints
dataForArmEvaluation	dataForArmEvaluation

Value

Arm

initialize, Combined1-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'Combined1'  
initialize(  
  .Object,  
  outcome,  
  equation,  
  derivatives,  
  sigmaInter,  
  sigmaSlope,  
  cError  
)
```

Arguments

.Object	.Object
outcome	outcome
equation	equation
derivatives	derivatives
sigmaInter	sigmaInter
sigmaSlope	sigmaSlope
cError	cError

Value

Combined1

initialize,Constant-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'Constant'
initialize(
  .Object,
  outcome,
  equation,
  derivatives,
  sigmaInter,
  sigmaSlope,
  cError
)
```

Arguments

.Object	.Object
outcome	outcome
equation	equation
derivatives	derivatives
sigmaInter	sigmaInter
sigmaSlope	sigmaSlope
cError	cError

Value

Constant

initialize,Design-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'Design'  
initialize(  
  .Object,  
  name,  
  size,  
  arms,  
  outcomesEvaluation,  
  outcomesGradient,  
  numberOfArms,  
  fim  
)
```

Arguments

.Object	.Object
name	name
size	size
arms	arms
outcomesEvaluation	outcomesEvaluation
outcomesGradient	outcomesGradient
numberOfArms	numberOfArms
fim	fim

Value

Design

```
initialize,Distribution-method
      initialize
```

Description

initialize

Usage

```
## S4 method for signature 'Distribution'
initialize(.Object, parameters)
```

Arguments

.Object	.Object
parameters	parameters

Value

Distribution

```
initialize,Evaluation-method
      initialize
```

Description

initialize

Usage

```
## S4 method for signature 'Evaluation'
initialize(
  .Object,
  name,
  model,
  modelEquations,
  modelParameters,
  modelError,
  outcomes,
  designs,
  fim,
  odeSolverParameters
)
```


Arguments

.Object	.Object
name	name
model	model
modelEquations	modelEquations
modelParameters	modelParameters
modelError	modelError
outcomes	outcomes
designs	designs
fim	fim
odeSolverParameters	odeSolverParameters

Value

Evaluation

initialize,FedorovWynnAlgorithm-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'FedorovWynnAlgorithm'
initialize(
  .Object,
  elementaryProtocols,
  numberOfSubjects,
  proportionsOfSubjects,
  showProcess
)
```

Arguments

.Object	.Object
elementaryProtocols	elementaryProtocols
numberOfSubjects	numberOfSubjects
proportionsOfSubjects	proportionsOfSubjects
showProcess	showProcess

Value

FedorovWynnAlgorithm

initialize,Fim-method initialize

Description

initialize

Usage

```
## S4 method for signature 'Fim'
initialize(.Object, fisherMatrix, fixedEffects, varianceEffects, shrinkage)
```

Arguments

.Object	.Object
fisherMatrix	fisherMatrix
fixedEffects	fixedEffects
varianceEffects	varianceEffects
shrinkage	shrinkage

Value

Fim

*initialize,LibraryOfModels-method
initialize*

Description

initialize

Usage

```
## S4 method for signature 'LibraryOfModels'
initialize(.Object, name, content)
```

Arguments

.Object	.Object
name	fisherMatrix
content	fixedEffects

Value

LibraryOfModels

initialize,LibraryOfPKPDMModels-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'LibraryOfPKPDMModels'  
initialize(.Object)
```

Arguments

.Object .Object

Value

LibraryOfPKPDMModels

initialize,LogNormal-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'LogNormal'  
initialize(.Object, ...)
```

Arguments

.Object .Object
... args

Value

LogNormal

```
initialize,Model-method
      initialize
```

Description

initialize

Usage

```
## S4 method for signature 'Model'
initialize(
  .Object,
  name,
  description,
  equations,
  outcomes,
  outcomesForEvaluation,
  parameters,
  modelError,
  initialConditions,
  odeSolverParameters,
  modelFromLibrary
)
```

Arguments

.Object	.Object
name	name
description	description
equations	equations
outcomes	outcomes
outcomesForEvaluation	outcomesForEvaluation
parameters	parameters
modelError	modelError
initialConditions	initialConditions
odeSolverParameters	odeSolverParameters
modelFromLibrary	modelFromLibrary

Value

Model

initialize,ModelAnalytic-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'ModelAnalytic'  
initialize(  
  .Object,  
  name,  
  description,  
  equations,  
  outcomes,  
  parameters,  
  modelError  
)
```

Arguments

.Object	.Object
name	name
description	description
equations	equations
outcomes	outcomes
parameters	parameters
modelError	modelError

Value

ModelAnalytic

initialize,ModelAnalyticBolus-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'ModelAnalyticBolus'
initialize(
  .Object,
  name,
  description,
  equations,
  outcomes,
  parameters,
  modelError
)
```

Arguments

.Object	.Object
name	name
description	description
equations	equations
outcomes	outcomes
parameters	parameters
modelError	modelError

Value

ModelAnalyticBolus

initialize,ModelAnalyticBolusSteadyState-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'ModelAnalyticBolusSteadyState'
initialize(
  .Object,
  name,
  description,
  equations,
  outcomes,
  parameters,
  modelError
)
```

Arguments

.Object	.Object
name	name
description	description
equations	equations
outcomes	outcomes
parameters	parameters
modelError	modelError

Value

ModelAnalyticBolusSteadyState

initialize,ModelAnalyticInfusion-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'ModelAnalyticInfusion'
initialize(
  .Object,
  name,
  description,
  equations,
  outcomes,
  parameters,
  modelError
)
```

Arguments

.Object	.Object
name	name
description	description
equations	equations
outcomes	outcomes
parameters	parameters
modelError	modelError

Value

ModelAnalyticInfusion

initialize,ModelAnalyticInfusionSteadyState-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'ModelAnalyticInfusionSteadyState'
initialize(
  .Object,
  name,
  description,
  equations,
  outcomes,
  parameters,
  modelError
)
```

Arguments

.Object	.Object
name	name
description	description
equations	equations
outcomes	outcomes
parameters	parameters
modelError	modelError

Value

ModelAnalyticInfusionSteadyState

initialize,ModelAnalyticSteadyState-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'ModelAnalyticSteadyState'  
initialize(  
  .Object,  
  name,  
  description,  
  equations,  
  outcomes,  
  parameters,  
  modelError  
)
```

Arguments

.Object	.Object
name	name
description	description
equations	equations
outcomes	outcomes
parameters	parameters
modelError	modelError

Value

ModelAnalyticSteadyState

initialize,ModelBolus-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'ModelBolus'  
initialize(  
  .Object,  
  name,  
  description,  
  equations,  
  outcomes,  
  parameters,  
  modelError,  
  initialConditions,  
  odeSolverParameters  
)
```

Arguments

.Object	.Object
name	name
description	description
equations	equations
outcomes	outcomes
parameters	parameters
modelError	modelError
initialConditions	initialConditions
odeSolverParameters	odeSolverParameters

Value

ModelBolus

initialize,ModelError-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'ModelError'
initialize(
  .Object,
  outcome,
  equation,
  derivatives,
  sigmaInter,
  sigmaSlope,
  cError
)
```

Arguments

.Object	.Object
outcome	outcome
equation	equation
derivatives	derivatives
sigmaInter	sigmaInter
sigmaSlope	sigmaSlope
cError	cError

Value

ModelError

initialize,ModelInfusion-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'ModelInfusion'
initialize(
  .Object,
  name,
  description,
  equations,
  outcomes,
  parameters,
  modelError,
```

```

    initialConditions,
    odeSolverParameters
)

```

Arguments

.Object	.Object
name	name
description	description
equations	equations
outcomes	outcomes
parameters	parameters
modelError	modelError
initialConditions	initialConditions
odeSolverParameters	odeSolverParameters

Value

ModelInfusion

initialize,ModelParameter-method
initialize

Description

initialize

Usage

```

## S4 method for signature 'ModelParameter'
initialize(.Object, name, distribution, fixedMu, fixedOmega)

```

Arguments

.Object	.Object
name	name
distribution	distribution
fixedMu	fixedMu
fixedOmega	fixedOmega

Value

ModelParameter

`initialize, MultiplicativeAlgorithm-method`
initialize

Description

`initialize`

Usage

```
## S4 method for signature 'MultiplicativeAlgorithm'  
initialize(  
  .Object,  
  arms,  
  lambda,  
  delta,  
  numberOfIterations,  
  weightThreshold,  
  optimalWeights,  
  optimalDesign,  
  showProcess  
)
```

Arguments

<code>.Object</code>	<code>.Object</code>
<code>arms</code>	<code>arms</code>
<code>lambda</code>	<code>lambda</code>
<code>delta</code>	<code>delta</code>
<code>numberOfIterations</code>	<code>numberOfIterations</code>
<code>weightThreshold</code>	<code>weightThreshold</code>
<code>optimalWeights</code>	<code>optimalWeights</code>
<code>optimalDesign</code>	<code>optimalDesign</code>
<code>showProcess</code>	<code>showProcess</code>

Value

`MultiplicativeAlgorithm`

```
initialize, Normal-method
      initialize
```

Description

initialize

Usage

```
## S4 method for signature 'Normal'
initialize(.Object, ...)
```

Arguments

.Object	.Object
...	args

Value

Normal

```
initialize, Optimization-method
      initialize
```

Description

initialize

Usage

```
## S4 method for signature 'Optimization'
initialize(
  .Object,
  name,
  model,
  modelEquations,
  modelParameters,
  modelError,
  optimizer,
  optimizerParameters,
  outcomes,
  designs,
  fim,
```

```

    odeSolverParameters,
    optimizationResults,
    evaluationFIMResults,
    evaluationInitialDesignResults
)

```

Arguments

.Object	.Object
name	name
model	model
modelEquations	modelEquations
modelParameters	modelParameters
modelError	modelError
optimizer	optimizer
optimizerParameters	optimizerParameters
outcomes	outcomes
designs	designs
fim	fim
odeSolverParameters	odeSolverParameters
optimizationResults	optimizationResults
evaluationFIMResults	evaluationFIMResults
evaluationInitialDesignResults	evaluationInitialDesignResults

Value

Optimization

```

initialize, OptimizationAlgorithm-method
      initialize

```

Description

initialize

Usage

```

## S4 method for signature 'OptimizationAlgorithm'
initialize(.Object, name, parameters)

```

Arguments

.Object	.Object
name	name
parameters	parameters

Value

OptimizationAlgorithm

initialize,PFIMProject-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'PFIMProject'
initialize(.Object, name, description)
```

Arguments

.Object	.Object
name	name
description	description

Value

PFIMProject

initialize,PGBOAlgorithm-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'PGBAlgorithm'  
initialize(  
  .Object,  
  N,  
  muteEffect,  
  maxIteration,  
  purgeIteration,  
  seed,  
  showProcess,  
  optimalDesign,  
  iterationAndCriteria  
)
```

Arguments

.Object	.Object
N	N
muteEffect	muteEffect
maxIteration	maxIteration
purgeIteration	purgeIteration
seed	seed
showProcess	showProcess
optimalDesign	optimalDesign
iterationAndCriteria	iterationAndCriteria

Value

PGBAlgorithm

initialize,Proportional-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'Proportional'
initialize(
  .Object,
  outcome,
  equation,
  derivatives,
  sigmaInter,
  sigmaSlope,
  cError
)
```

Arguments

.Object	.Object
outcome	outcome
equation	equation
derivatives	derivatives
sigmaInter	sigmaInter
sigmaSlope	sigmaSlope
cError	cError

Value

Proportional

initialize,PSOAlgorithm-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'PSOAlgorithm'
initialize(
  .Object,
  maxIteration,
  populationSize,
  personalLearningCoefficient,
  globalLearningCoefficient,
  seed,
  showProcess,
```

```

    optimalDesign,
    iterationAndCriteria
)

```

Arguments

.Object	.Object
maxIteration	maxIteration
populationSize	populationSize
personalLearningCoefficient	personalLearningCoefficient
globalLearningCoefficient	globalLearningCoefficient
seed	seed
showProcess	showProcess
optimalDesign	optimalDesign
iterationAndCriteria	iterationAndCriteria

Value

PSOAlgorithm

```

initialize, SamplingTimeConstraints-method
      initialize

```

Description

initialize

Usage

```

## S4 method for signature 'SamplingTimeConstraints'
initialize(
  .Object,
  outcome,
  initialSamplings,
  fixedTimes,
  numberOfSamplingsOptimisable,
  samplingsWindows,
  numberOfTimesByWindows,
  minSampling
)

```

Arguments

.Object	.Object
outcome	outcome
initialSamplings	initialSamplings
fixedTimes	fixedTimes
numberOfSamplingsOptimisable	numberOfSamplingsOptimisable
samplingsWindows	samplingsWindows
numberOfTimesByWindows	numberOfTimesByWindows
minSampling	minSampling

Value

SamplingTimeConstraints

initialize, SamplingTimes-method
initialize

Description

initialize

Usage

```
## S4 method for signature 'SamplingTimes'
initialize(.Object, outcome, samplings)
```

Arguments

.Object	.Object
outcome	outcome
samplings	samplings

Value

SamplingTimes

```
initialize, SimplexAlgorithm-method
      initialize
```

Description

initialize

Usage

```
## S4 method for signature 'SimplexAlgorithm'
initialize(
  .Object,
  pctInitialSimplexBuilding,
  maxIteration,
  tolerance,
  optimalDesigns,
  iterationAndCriteria,
  showProcess
)
```

Arguments

.Object	.Object
pctInitialSimplexBuilding	pctInitialSimplexBuilding
maxIteration	maxIteration
tolerance	tolerance
optimalDesigns	optimalDesigns
iterationAndCriteria	iterationAndCriteria
showProcess	showProcess

Value

SimplexAlgorithm

isDoseInEquations *Test if the dose is in the equations of the model.*

Description

Test if the dose is in the equations of the model.

Usage

```
isDoseInEquations(object)

## S4 method for signature 'Model'
isDoseInEquations(object)
```

Arguments

object An object from the class [Model](#).

Value

Return a Boolean giving if the dose is in the equations of the model.

isModelAnalytic *Test if a mode is analytic.*

Description

Test if a mode is analytic.

Usage

```
isModelAnalytic(object)

## S4 method for signature 'Model'
isModelAnalytic(object)
```

Arguments

object An object from the class [Model](#).

Value

Return a Boolean giving if the mode is analytic or not.

isModelBolus	<i>Test if a mode is bolus.</i>
--------------	---------------------------------

Description

Test if a mode is bolus.

Usage

```
isModelBolus(object, designs)
```

```
## S4 method for signature 'Model'  
isModelBolus(object, designs)
```

Arguments

object	An object from the class Model .
designs	A list of objects from the class Design .

Value

Return a Boolean giving if the mode is bolus or not.

isModelInfusion	<i>Test if a mode is infusion</i>
-----------------	-----------------------------------

Description

Test if a mode is infusion

Usage

```
isModelInfusion(object)
```

```
## S4 method for signature 'Model'  
isModelInfusion(object)
```

Arguments

object	An object from the class Model .
--------	--

Value

Return a Boolean giving if the mode is infusion or not.

isModelODE	<i>Test if a mode is ode.</i>
------------	-------------------------------

Description

Test if a mode is ode.

Usage

```
isModelODE(object)
```

```
## S4 method for signature 'Model'  
isModelODE(object)
```

Arguments

object An object from the class [Model](#).

Value

Return a Boolean giving if the mode is ode or not.

isModelSteadyState	<i>Test if a mode is steady state.</i>
--------------------	--

Description

Test if a mode is steady state.

Usage

```
isModelSteadyState(object)
```

```
## S4 method for signature 'Model'  
isModelSteadyState(object)
```

Arguments

object An object from the class [Model](#).

Value

Return a Boolean giving if the mode is steady state or not.

LibraryOfModels-class *Class "LibraryOfModels"*

Description

The class LibraryOfModels represents the library of models.

Objects from the class

Objects from the class LibraryOfModels can be created by calls of the form LibraryOfModels(...) where (...) are the parameters for the LibraryOfModels objects.

Slots for LibraryOfModels objects

name: A string giving the name of the library of models.

content: A list giving the content of the library of model.

LibraryOfPDModels *Library of the PK models*

Description

Library of the PK models

Usage

LibraryOfPDModels()

LibraryOfPKModels *Library of the PK models*

Description

Library of the PK models

Usage

LibraryOfPKModels()

LibraryOfPKPDModels-class
Class "LibraryOfPKPDModels"

Description

The class `LibraryOfPKPDModels` represents the library of PKPD models. The class `LibraryOfPKPDModels` inherits from the class `LibraryOfModels`.

LogNormal-class *Class "LogNormal"*

Description

The class defines all the required methods for a `LogNormal` distribution object. The class `LogNormal` inherits from the class `Distribution`.

Model-class *Class "Model"*

Description

The class `Model` defines information concerning the construction of a model.

Objects from the class

Objects from the class `Model` can be created by calls of the form `Model(...)` where (...) are the parameters for the `Model` objects.

Slots for Administration objects

name: A string giving the name of the model.
description: A list of string giving the description of the model.
equations: A list giving the equations of the model.
outcomes: A list giving the outcomes of the model.
outcomesForEvaluation: A list giving the outcomes used for the evaluation of the model.
parameters: A list giving the parameters of the model.
modelError: A list giving the model error of the model.
initialConditions: A list giving the initial conditions of the model.
odeSolverParameters: A list giving the parameters for the solver of the model.
modelFromLibrary: A list giving the model equations when the model is constructed from the library of model.

ModelAnalytic-class *Class "ModelAnalytic"*

Description

The class Model defines information concerning the construction of an analytical model. The class ModelAnalytic inherits from the class Model.

ModelAnalyticBolus-class
 Class "ModelAnalyticBolus"

Description

The class Model defines information concerning the construction of an analytical bolus model. The class ModelAnalyticBolus inherits from the class ModelAnalytic.

ModelAnalyticBolusSteadyState-class
 Class "ModelAnalyticBolusSteadyState"

Description

The class Model defines information concerning the construction of an analytical model in steady state. The class ModelAnalyticBolusSteadyState inherits from the class ModelAnalyticSteadyState.

ModelAnalyticInfusion-class
 Class "ModelAnalyticInfusion"

Description

The class Model defines information concerning the construction of an analytical model in infusion. The class ModelAnalyticInfusion inherits from the class ModelInfusion.

ModelAnalyticInfusionSteadyState-class
Class "ModelAnalyticInfusionSteadyState"

Description

The class Model defines information concerning the construction of an analytical model in infusion in steady state. The class ModelAnalyticInfusionSteadyState inherits from the class ModelAnalyticInfusion.

ModelAnalyticSteadyState-class
Class "ModelAnalyticSteadyState"

Description

The class ModelAnalyticSteadyState defines information concerning the construction of an analytical model steady state. The class ModelAnalyticSteadyState inherits from the class ModelAnalytic.

ModelBolus-class *Class "ModelBolus"*

Description

...

ModelError-class *Class "ModelError" representing a Model error.*

Description

...

ModelInfusion-class *Class "ModelInfusion"*

Description

...

ModelODE-class *Class "ModelODE"*

Description

The class ModelODE defines information concerning the construction of an ode model. The class ModelODE inherits from the class Model.

ModelODEDoseInEquations-class
 Class "ModelODEDoseInEquations"

Description

The class ModelODEDoseInEquations defines information concerning the construction of an ode model where the dose is in the model equations. The class ModelODEDoseInEquations inherits from the class ModelODE.

ModelODEDoseNotInEquations-class
 Class "ModelODEDoseNotInEquations"

Description

...

ModelODEInfusion-class
 Class "ModelODEInfusion"

Description

The class ModelODEInfusion defines information concerning the construction of an ode model in infusion. The class ModelODEInfusion inherits from the class ModelInfusion.

 ModelODEInfusionDoseInEquations-class

Class "ModelODEInfusionDoseInEquations"

Description

The class ModelODEInfusionDoseInEquations defines information concerning the construction of an ode model in infusion where the dose is in the model equations. The class ModelODEInfusionDoseInEquations inherits from the class ModelODEInfusion.

 ModelParameter-class *Class "ModelParameter"*

Description

The class ModelParameter defines information concerning the model parameters.

Objects from the class

Objects from the class ModelParameter can be created by calls of the form ModelParameter(...) where (...) are the parameters for the ModelParameter objects.

Slots for ModelParameter objects

name: A string giving the name of the parameter.

distribution: An object from the class Distribution giving the distribution of the parameter.

fixedMu: A boolean giving if mu is fixed or not.

fixedOmega: A boolean giving if omega is fixed or not.

 MultiplicativeAlgorithm-class

Class "MultiplicativeAlgorithm"

Description

The class MultiplicativeAlgorithm implements the multiplicative algorithm.

Objects from the class

Objects from the class MultiplicativeAlgorithm can be created by calls of the form MultiplicativeAlgorithm(...) where (...) are the parameters for the MultiplicativeAlgorithm objects.

Slots for MultiplicativeAlgorithm objects

arms: A list giving the arms.

lambda: A numeric giving the lambda parameter of the multiplicative algorithm.

delta: A numeric giving the delta parameter of the multiplicative algorithm.

numberOfIterations: A numeric giving the maximal number iteration of the optimization process.

weightThreshold: A numeric giving the threshold of the weights.

optimalWeights: A vector giving the optimal weights.

optimalDesign: An object of the class Design giving the optimal design.

showProcess: A boolean for showing or not the process of optimization.

MultiplicativeAlgorithm_Rcpp

Function MultiplicativeAlgorithm_Rcpp

Description

Run the MultiplicativeAlgorithm_Rcpp in Rcpp

Usage

```
MultiplicativeAlgorithm_Rcpp(
  fisherMatrices_input,
  numberOfFisherMatrices_input,
  weights_input,
  numberOfParameters_input,
  dim_input,
  lambda_input,
  delta_input,
  iterationInit_input
)
```

Arguments

```
fisherMatrices_input      fisherMatrices_input
numberOfFisherMatrices_input  numberOfFisherMatrices_input
weights_input             weights_input
numberOfParameters_input  numberOfParameters_input
dim_input                 dim_input
lambda_input              lambda_input
```

```

delta_input    delta_input
iterationInit_input
                iterationInit_input

```

Normal-class *Class "Normal"*

Description

The class defines all the required methods for a Normal distribution object. The class Normal inherits from the class Distribution.

Optimization-class *Class "Optimization"*

Description

A class storing information concerning the design optimization.

Objects from the class

Objects from the class Optimization can be created by calls of the form Optimization(...) where (...) are the parameters for the Optimization objects.

Slots for Administration objects

name: A character string giving the name of the optimization process.
model: A object of class Model giving the model.
modelEquations: A list giving the model equations.
modelParameters: A list giving the model parameters.
modelError: A list giving the model error.
optimizer: A object of class OptimizationAlgorithm giving the optimization algorithm.
optimizerParameters: A list giving the parameters of the optimization algorithm.
outcomes: A list giving the outcomes of the model.
designs: A list giving the designs to be optimized.
fim: A object of class FIM giving the Fisher information matrix.
odeSolverParameters: A list giving the parameters for the ode solver.
optimizationResults: A object of class OptimizationAlgorithm giving the results of the optimization.
evaluationFIMResults: A object of class Evaluation giving the results of the evaluation of the optimal design.
evaluationInitialDesignResults: A object of class Evaluation giving the results of the evaluation of the initial design.

OptimizationAlgorithm-class
Class "OptimizationAlgorithm"

Description

A class storing information concerning the optimization algorithm.

Objects from the class

Objects from the class `OptimizationAlgorithm` can be created by calls of the form `OptimizationAlgorithm(...)` where (...) are the parameters for the `OptimizationAlgorithm` objects.

Slots for Administration objects

name: A character string giving the name of the optimization algorithm.

parameters: A list giving the parameters of the optimization algorithm.

optimize	<i>Optimize a design.</i>
----------	---------------------------

Description

Optimize a design.

Usage

```
optimize(object, optimizerParameters, optimizationObject)
```

```
## S4 method for signature 'FedorovWynnAlgorithm'
optimize(object, optimizerParameters, optimizationObject)
```

```
## S4 method for signature 'MultiplicativeAlgorithm'
optimize(object, optimizerParameters, optimizationObject)
```

```
## S4 method for signature 'PGBAlgorithm'
optimize(object, optimizationObject)
```

```
## S4 method for signature 'PSOAlgorithm'
optimize(object, optimizationObject)
```

```
## S4 method for signature 'SimplexAlgorithm'
optimize(object, optimizerParameters, optimizationObject)
```

Arguments

object	An object from the class OptimizationAlgorithm .
optimizerParameters	A list giving the optimization parameters.
optimizationObject	An object giving the optimization algorithm.

Value

A list giving the results if the optimization.

parametersForComputingGradient

Define the parameters for computing the gradients of a model.

Description

Define the parameters for computing the gradients of a model.

Usage

```
parametersForComputingGradient(object, valuePars)
```

```
## S4 method for signature 'Model'
parametersForComputingGradient(object, valuePars)
```

Arguments

object	An object from the class Model .
valuePars	Vector of parameter values

Value

A list giving the parameters for computing the gradients of a model.

PFIMProject-class *Class "PFIMProject"*

Description

A class storing information concerning a PFIM project.

Objects from the class

Objects from the class PFIMProject can be created by calls of the form PFIMProject(...) where (...) are the parameters for the PFIMProject objects.

Slots for PFIMProject objects

name: A character string giving the name of the PFIM project.

description: A list giving the description of the PFIM project.

PGBAlgorithm-class *Class "PGBAlgorithm"*

Description

The class "PGBAlgorithm" implements the PGB algorithm: Population Genetics Based Optimizer, developed by Hervé Le Nagard [1].

Objects from the Class PGBAlgorithm

Objects from the Class PGBAlgorithm can be created by calls of the form PGBAlgorithm(...) where (...) are the parameters for the PGBAlgorithm objects.

Slots for PGBAlgorithm objects

N: A numeric giving the population size.

muteEffect: A numeric giving the mutation effect.

maxIteration: A numeric giving the maximum number of iterations.

seed: A numeric giving the seed.

showProcess: A boolean to show or not the process.

optimalDesign: A Design object giving the optimal design.

iterationAndCriteria: A list giving the optimal criteria at each iteration.

References

[1] Rebecca Bauer, France Mentré, Halima Kaddouri, Jacques Le Bras, Hervé Le Nagard, Benefits of a new Metropolis-Hasting based algorithm, in non-linear regression for estimation of ex vivo antimalarial sensitivity in patients infected with two strains, Computers in Biology and Medicine, Volume 55, 2014, Pages 16-25, ISSN 0010-4825

plotEvaluation *Graphs of the results of the evaluation.*

Description

Graphs of the results of the evaluation.

Usage

```
plotEvaluation(object, plotOptions)

## S4 method for signature 'Evaluation'
plotEvaluation(object, plotOptions)
```

Arguments

object An object from the class [Evaluation](#).
plotOptions A list giving the plot options.

Value

A list giving the graphs for the evaluation of the responses and sensitivity indices.

PlotEvaluation-class *Class "PlotEvaluation"*

Description

A class storing information concerning the design evaluation. The class PlotEvaluation inherits from the class Evaluation.

plotFrequencies *Graph of the frequencies for the FW algorithm.*

Description

Graph of the frequencies for the FW algorithm.

Usage

```
plotFrequencies(object)

## S4 method for signature 'FedorovWynnAlgorithm'
plotFrequencies(object)

## S4 method for signature 'Optimization'
plotFrequencies(object)
```

Arguments

object An object from the class [OptimizationAlgorithm](#).

Value

The graphs of the frequencies for the FW algorithm.

```
plotOutcomesEvaluation
                          plotOutcomesEvaluation
```

Description

Plot the evaluation of the outcomes.

Usage

```
plotOutcomesEvaluation(
  object,
  outcomesEvaluationInitialDesign,
  model,
  plotOptions
)

## S4 method for signature 'Design'
plotOutcomesEvaluation(
  object,
  outcomesEvaluationInitialDesign,
  model,
  plotOptions
)
```

Arguments

object An object Design from the class [Design](#).
outcomesEvaluationInitialDesign
 A list containing the evaluation of the initial design.

model An object model from the class [Model](#).
 plotOptions A list containing the plot options.

Value

A list containing the plots the evaluation of the outcomes.

plotOutcomesGradient *plotOutcomesGradient*

Description

Plot the evaluation of the outcome gradients.

Usage

```
plotOutcomesGradient(object, outcomesGradientInitialDesign, model, plotOptions)

## S4 method for signature 'Design'
plotOutcomesGradient(object, outcomesGradientInitialDesign, model, plotOptions)
```

Arguments

object An object design from the class [Design](#).
 outcomesGradientInitialDesign
 A list with the evaluation of the gradient for the initial design.
 model An object model from the class [Model](#).
 plotOptions A list containing the plot options.

Value

A list containing the plots the evaluation of the outcome gradients..

plotRSE *Graph of the RSE.*

Description

Graph of the RSE.

Usage

```
plotRSE(object, plotOptions)

## S4 method for signature 'PFIMProject'
plotRSE(object, plotOptions)
```

Arguments

object An object from the class [Evaluation](#).
plotOptions A list giving the plot options.

Value

A graph of the RSE.

plotSE *Graph the SE.*

Description

Graph the SE.

Usage

```
plotSE(object, plotOptions)  
  
## S4 method for signature 'PFIMProject'  
plotSE(object, plotOptions)
```

Arguments

object An object from the class [Evaluation](#).
plotOptions A list giving the plot options.

Value

A graph of the SE.

plotSensitivityIndice *Graphs of the results of the evaluation.*

Description

Graphs of the results of the evaluation.

Usage

```
plotSensitivityIndice(object, plotOptions)  
  
## S4 method for signature 'Evaluation'  
plotSensitivityIndice(object, plotOptions)
```

Arguments

object An object from the class [Evaluation](#).
 plotOptions A list giving the plot options.

Value

A list giving the graphs for the evaluation of the responses and sensitivity indices.

plotShrinkage *Graph of the shrinkage.*

Description

Graph of the shrinkage.

Usage

```
plotShrinkage(object, plotOptions)

## S4 method for signature 'PFIMProject'
plotShrinkage(object, plotOptions)
```

Arguments

object An object from the class [Evaluation](#).
 plotOptions A list giving the plot options.

Value

A graph of the shrinkage.

plotWeights *Graph of the weights for the multiplicative algorithm.*

Description

Graph of the weights for the multiplicative algorithm.

Usage

```
plotWeights(object)

## S4 method for signature 'MultiplicativeAlgorithm'
plotWeights(object)

## S4 method for signature 'Optimization'
plotWeights(object)
```


Arguments

object An object from the class [OptimizationAlgorithm](#).

Value

The graphs of the weights for the multiplicative algorithm.

PopulationFim-class *Class "PopulationFim"*

Description

A class storing information regarding the population Fisher matrix. The class PopulationFim inherits from the class Fim.

Proportional-class *Class "Proportional"*

Description

The Class "Proportional" defines the the residual error variance according to the formula $g(\text{sigma_inter}, \text{sigma_slope}, \text{c_error}, f(x, \text{theta})) = \text{sigma_slope} * f(x, \text{theta})$.

Objects from the Class [Proportional](#)

Objects are typically created by calls to Proportional and contain the following slots that are inherited from the class [Combined1](#):

Slots for the Proportional objects

.Object: An object of the Class Proportional

sigma_inter: A numeric value giving the sigma inter of the error model

sigma_slope: A numeric value giving the sigma slope of the error model

PSOAlgorithm-class *Class "PSOAlgorithm"*

Description

The class "PSOAlgorithm" implements the PSO algorithm.

Objects from the class PSOAlgorithm

Objects from the class PSOAlgorithm can be created by calls of the form PSOAlgorithm(...) where (...) are the parameters for the PSOAlgorithm objects.

Slots for PSOAlgorithm objects

maxIteration: A numeric giving the maximum of iterations.
populationSize: A numeric giving the population size.
seed: A numeric giving the seed.
personalLearningCoefficient: A numeric giving the personal learning coefficient.
globalLearningCoefficient: A numeric giving the global learning coefficient.
showProcess: A boolean to show or not the process.
optimalDesign: A Design object giving the optimal design.
iterationAndCriteria: A list giving the optimal criteria at each iteration.

Report

Report

Description

Report

Usage

```
Report(object, outputPath, outputFile, plotOptions)

## S4 method for signature 'Evaluation'
Report(object, outputPath, outputFile, plotOptions)

## S4 method for signature 'Optimization'
Report(object, outputPath, outputFile, plotOptions)
```

Arguments

object	An object from the class PFIMProject .
outputPath	A string giving the output path.
outputFile	A string giving the name of the output file.
plotOptions	A list giving the plot options.

Value

The report in html.

```
reportTablesAdministration
      reportTablesAdministration
```

Description

Generate table for the report.

Usage

```
reportTablesAdministration(object)

## S4 method for signature 'Design'
reportTablesAdministration(object)
```

Arguments

object	An object design from the class Design .
--------	--

Value

A table of the administration parameters for the report.

```
reportTablesDesign      reportTablesDesign
```

Description

Generate table for the report.

Usage

```
reportTablesDesign(object)

## S4 method for signature 'Design'
reportTablesDesign(object)
```

Arguments

object An object design from the class [Design](#).

Value

A table of the design parameters for the report.

reportTablesFIM *Generate the tables for the report.*

Description

Generate the tables for the report.

Usage

```
reportTablesFIM(object, evaluationObject)

## S4 method for signature 'BayesianFim'
reportTablesFIM(object, evaluationObject)

## S4 method for signature 'IndividualFim'
reportTablesFIM(object, evaluationObject)

## S4 method for signature 'PopulationFim'
reportTablesFIM(object, evaluationObject)
```

Arguments

object An object from the class [Fim](#).
evaluationObject A list giving the results of the evaluation of the model.

Value

A list giving the table in kable format for the report.

`reportTablesModelError`*Generate the tables for model errors for the evaluation report.*

Description

Generate the tables for model errors for the evaluation report.

Usage

```
reportTablesModelError(object)
```

```
## S4 method for signature 'Model'  
reportTablesModelError(object)
```

Arguments

`object` An object from the class [Model](#).

Value

A kable table for the evaluation report.

`reportTablesModelParameters`*Generate the tables for model parameters for the evaluation report.*

Description

Generate the tables for model parameters for the evaluation report.

Usage

```
reportTablesModelParameters(object)
```

```
## S4 method for signature 'Model'  
reportTablesModelParameters(object)
```

Arguments

`object` An object from the class [Model](#).

Value

A kable table for the evaluation report.

reportTablesPlot	<i>reportTablesPlot</i>
------------------	-------------------------

Description

Generate all the table for the evaluation report

Usage

```
reportTablesPlot(object, plotOptions)

## S4 method for signature 'Evaluation'
reportTablesPlot(object, plotOptions)
```

Arguments

object	An object evaluation from the class Evaluation .
plotOptions	A list containing the options for the plots.

Value

The list tables containing the tables for the evaluation report.

reportTablesSamplingConstraints	<i>reportTablesSamplingConstraints</i>
---------------------------------	--

Description

Generate table for the report.

Usage

```
reportTablesSamplingConstraints(object)

## S4 method for signature 'Design'
reportTablesSamplingConstraints(object)
```

Arguments

object	An object design from the class Design .
--------	--

Value

A table of the sampling constraints parameters for the report.

resizeFisherMatrix	<i>Resize the fisher Matrix from a vector to a matrix.</i>
--------------------	--

Description

Resize the fisher Matrix from a vector to a matrix.

Usage

```
resizeFisherMatrix(nbOfDimensions, fisherMatrix)
```

```
## S4 method for signature 'ANY'
```

```
resizeFisherMatrix(nbOfDimensions, fisherMatrix)
```

Arguments

`nbOfDimensions` : a numeric for the dimensions of the fisher matrix.

`fisherMatrix` : a vector that contain the low triangular Fisher matrix + its main diagonal.

Value

The Fisher matrix of size `nbOfDimensions*nbOfDimensions`

run	<i>run</i>
-----	------------

Description

run

Usage

```
run(object)
```

```
## S4 method for signature 'Evaluation'
```

```
run(object)
```

```
## S4 method for signature 'Optimization'
```

```
run(object)
```

Arguments

`object` : An object from the class [PFIMProject](#).

Value

A list giving the results of evaluation or optimization.

SamplingTimeConstraints-class
Class "SamplingTimeConstraints"

Description

The class "SamplingTimeConstraints" implements the constraints for the sampling times.

Objects from the class SamplingTimeConstraints

Objects from the class SamplingTimeConstraints can be created by calls of the form SamplingTimeConstraints(...) where (...) are the parameters for the SamplingTimeConstraints objects.

Slots for SamplingTimeConstraints objects

outcome: A string giving the outcome.

initialSamplings: A vector giving the sampling times.

fixedTimes: A vector giving the fixed sampling times.

numberOfSamplingsOptimisable: A vector giving the sampling times to be optimized.

samplingsWindows: A list giving the windows for the sampling times.

numberOfTimesByWindows: A vector giving the number of sampling times by windows.

minSampling: A numeric giving the minimal sampling times.

SamplingTimes-class *Class "SamplingTimes"*

Description

The class "SamplingTimes" implements the sampling times.

Objects from the class SamplingTimes

Objects from the class SamplingTimes can be created by calls of the form SamplingTimes(...) where (...) are the parameters for the SamplingTimes objects.

Slots for SamplingTimes objects

outcome: A string giving the outcome.

samplings: A vector giving the sampling times.

setAdministrations	<i>setAdministrations</i>
--------------------	---------------------------

Description

Set all the administration for an arm.

Usage

```
setAdministrations(object, administrations)
```

```
## S4 method for signature 'Arm'
setAdministrations(object, administrations)
```

Arguments

object An object Arm from the class [Arm](#).

administrations

A list administrations of objects from the class Administration class giving the parameters of the administration for the object Arm.

Value

The object Arm with the list administrations of objects from the class Administration class giving the parameters of the administration for the object Arm.

setArm	<i>setArm</i>
--------	---------------

Description

Set the arms in a design.

Usage

```
setArm(object, arm)
```

```
## S4 method for signature 'Design'
setArm(object, arm)
```

Arguments

object An object Design from the class [Design](#).

arm

A list of object Arm giving the arms of the design.

Value

An object Design with the list Arm updated.

setArms	<i>Set the arms of an object.</i>
---------	-----------------------------------

Description

Set the arms of an object.

Usage

```
setArms(object, arms)
```

```
## S4 method for signature 'Design'  
setArms(object, arms)
```

```
## S4 method for signature 'OptimizationAlgorithm'  
setArms(object, arms)
```

Arguments

object	An object defined form a class of PFIM.
arms	A list of arms.

Value

The object with the updated arms.

setcError	<i>Set the parameter c.</i>
-----------	-----------------------------

Description

Set the parameter c.

Usage

```
setcError(object, cError)
```

```
## S4 method for signature 'ModelError'  
setcError(object, cError)
```

Arguments

object	An object from the class ModelError .
cError	A numeric giving the parameter c.

Value

The model error with the parameter c.

setContent	<i>Set content of a library of models.</i>
------------	--

Description

Set content of a library of models.

Usage

```
setContent(object, content)
```

```
## S4 method for signature 'LibraryOfModels'
```

```
setContent(object, content)
```

Arguments

object An object from the class [LibraryOfModels](#).

content A list giving the content of the library of models.

Value

The library of models with the updated content.

setDataForArmEvaluation	<i>setDataForArmEvaluation</i>
-------------------------	--------------------------------

Description

setDataForArmEvaluation

Usage

```
setDataForArmEvaluation(object, data)
```

```
## S4 method for signature 'Arm'
```

```
setDataForArmEvaluation(object, data)
```

Arguments

object An object Arm from the class [Arm](#).

data A list containing the data for arm evaluation

Value

Set the list containing the data for arm evaluation.

```
setDataForModelEvaluation
```

Generate the table of dose, time dose etc. for model evaluation

Description

Generate the table of dose, time dose etc. for model evaluation

Usage

```
setDataForModelEvaluation(object, arm)

## S4 method for signature 'ModelAnalytic'
setDataForModelEvaluation(object, arm)

## S4 method for signature 'ModelAnalyticSteadyState'
setDataForModelEvaluation(object, arm)

## S4 method for signature 'ModelAnalyticInfusion'
setDataForModelEvaluation(object, arm)

## S4 method for signature 'ModelAnalyticInfusionSteadyState'
setDataForModelEvaluation(object, arm)

## S4 method for signature 'ModelODEBolus'
setDataForModelEvaluation(object, arm)

## S4 method for signature 'ModelODEDoseInEquations'
setDataForModelEvaluation(object, arm)

## S4 method for signature 'ModelODEDoseNotInEquations'
setDataForModelEvaluation(object, arm)

## S4 method for signature 'ModelODEInfusionDoseInEquations'
setDataForModelEvaluation(object, arm)
```

Arguments

object	An object from the class Model .
arm	An object from the class Arm .

Value

Return a dataframe with all the data for model evaluation

setDerivatives	<i>Set the derivatives of the model error equation.</i>
----------------	---

Description

Set the derivatives of the model error equation.

Usage

```
setDerivatives(object, derivatives)

## S4 method for signature 'ModelError'
setDerivatives(object, derivatives)
```

Arguments

object	An object from the class ModelError .
derivatives	The derivatives of the model error equation.

Value

The model error with the updated model error equation.

setDescription	<i>Set the description of a model.</i>
----------------	--

Description

Set the description of a model.

Usage

```
setDescription(object, description)

## S4 method for signature 'Model'
setDescription(object, description)
```

Arguments

object	An object from the class Model .
description	A list giving the description of a model.

Value

The model with the updated description.

setDesigns	<i>Set the designs.</i>
------------	-------------------------

Description

Set the designs.

Usage

```
setDesigns(object, designs)

## S4 method for signature 'Optimization'
setDesigns(object, designs)
```

Arguments

object	An object from the class Optimization .
designs	A list of objects from the class Design .

Value

The object with the new designs.

setDistribution	<i>Set the distribution.</i>
-----------------	------------------------------

Description

Set the distribution.

Usage

```
setDistribution(object, distribution)

## S4 method for signature 'ModelParameter'
setDistribution(object, distribution)
```

Arguments

object	An object from the class ModelParameter .
distribution	An object from the class Distribution .

Value

The model parameter with the updated distribution.

setDose	<i>Set the amount of dose</i>
---------	-------------------------------

Description

Set the amount of dose

Usage

```
setDose(object, dose)

## S4 method for signature 'Administration'
setDose(object, dose)
```

Arguments

object	An object Administration from the class Administration .
dose	A numeric value of the amount of dose.

Value

The numeric amount_dose giving the new value of the amount of dose.

setEquation	<i>Set the equation of a model error.</i>
-------------	---

Description

Set the equation of a model error.

Usage

```
setEquation(object, equation)

## S4 method for signature 'ModelError'
setEquation(object, equation)
```

Arguments

object	An object from the class ModelError .
equation	An expression giving the equation of a model error.

Value

The model error with the updated equation.

setEquations	<i>Set the equations of a model.</i>
--------------	--------------------------------------

Description

Set the equations of a model.

Usage

```
setEquations(object, equations)
```

```
## S4 method for signature 'Model'  
setEquations(object, equations)
```

Arguments

object	An object from the class Model .
equations	A list giving the equations of the model.

Value

The model with the updated equations.

setEquationsAfterInfusion	<i>Set the equations after infusion.</i>
---------------------------	--

Description

Set the equations after infusion.

Usage

```
setEquationsAfterInfusion(object, equations)
```

```
## S4 method for signature 'Model'  
setEquationsAfterInfusion(object, equations)
```

Arguments

object	An object from the class Model .
equations	A list giving the equations after the infusion.

Value

The model with the updated equations after the infusion.

```
setEquationsDuringInfusion
    Set the equations during infusion.
```

Description

Set the equations during infusion.

Usage

```
setEquationsDuringInfusion(object, equations)

## S4 method for signature 'Model'
setEquationsDuringInfusion(object, equations)
```

Arguments

object	An object from the class Model .
equations	A list giving the equations during the infusion.

Value

The model with the updated equations during the infusion.

```
setEvaluationFIMResults
    Set the evaluation results.
```

Description

Set the evaluation results.

Usage

```
setEvaluationFIMResults(object, value)

## S4 method for signature 'Optimization'
setEvaluationFIMResults(object, value)
```

Arguments

object	An object from the class Optimization .
value	An object from the class Evaluation giving the evaluation results.

Value

The object with the updated object from the class [Evaluation](#).

```
setEvaluationInitialDesignResults
```

Set the evaluation results of the initial design.

Description

Set the evaluation results of the initial design.

Usage

```
setEvaluationInitialDesignResults(object, value)
```

```
## S4 method for signature 'Optimization'
setEvaluationInitialDesignResults(object, value)
```

Arguments

object	An object from the class Optimization .
value	An object from the class Evaluation giving the evaluation results of the initial design.

Value

The object with the updated object from the class [Evaluation](#).

```
setFim
```

setFim

Description

Set the fim of the design.

Usage

```
setFim(object, fim)
```

```
## S4 method for signature 'Design'
setFim(object, fim)
```

Arguments

object	An object Design from the class Design .
fim	An object fim from the class Fim .

Value

An object Design with the fim updated.

setFimTypeToString	<i>Convert the type of the object fim to a string.</i>
--------------------	--

Description

Convert the type of the object fim to a string.

Usage

```
setFimTypeToString(object)
```

```
## S4 method for signature 'Fim'  
setFimTypeToString(object)
```

Arguments

object	An object from the class Fim .
--------	--

Value

The type of the object fim convert as a string.

setFisherMatrix	<i>Set the FIM.</i>
-----------------	---------------------

Description

Set the FIM.

Usage

```
setFisherMatrix(object, value)
```

```
## S4 method for signature 'Fim'  
setFisherMatrix(object, value)
```

Arguments

object	An object from the class Fim .
value	A matrix giving the FIM.

Value

The object from the class [Fim](#) with the FIM updated.

setFixedEffects	<i>Set the fixed effects.</i>
-----------------	-------------------------------

Description

Set the fixed effects.

Usage

```
setFixedEffects(object)

## S4 method for signature 'Fim'
setFixedEffects(object)
```

Arguments

object An object from the class [Fim](#).

Value

Update the matrix of the fixed effects.

setFixedMu	<i>Set the mu as fixed or not.</i>
------------	------------------------------------

Description

Set the mu as fixed or not.

Usage

```
setFixedMu(object, value)

## S4 method for signature 'ModelParameter'
setFixedMu(object, value)
```

Arguments

object An object from the class [ModelParameter](#).
value A Boolean if fixed or not.

Value

The mode parameter with the the mu updated as fixed or not.

setFixedOmega	<i>Set the omega as fixed of not.</i>
---------------	---------------------------------------

Description

Set the omega as fixed of not.

Usage

```
setFixedOmega(object, value)

## S4 method for signature 'ModelParameter'
setFixedOmega(object, value)
```

Arguments

object	An object from the class ModelParameter .
value	A Boolean fixed or not.

Value

The model parameter with the omega updated as fixed or not.

setInitialConditions	<i>setInitialConditions</i>
----------------------	-----------------------------

Description

Set the initial conditions of a ode model.

Usage

```
setInitialConditions(object, initialConditions)

## S4 method for signature 'Arm'
setInitialConditions(object, initialConditions)

## S4 method for signature 'Model'
setInitialConditions(object, initialConditions)
```

Arguments

object	An object from the class Model .
initialConditions	A list giving the initial conditions.

Value

The model with the updated initial conditions.

```
setIterationAndCriteria
```

Set the iteration with the convergence criteria.

Description

Set the iteration with the convergence criteria.

Usage

```
setIterationAndCriteria(object, value)
```

```
## S4 method for signature 'OptimizationAlgorithm'
setIterationAndCriteria(object, value)
```

Arguments

object	An object from the class OptimizationAlgorithm .
value	A dataframe giving the iteration with the convergence criteria.

Value

A dataframe giving the iteration with the convergence criteria.

```
setModel
```

Set the model.

Description

Set the model.

Usage

```
setModel(object, model)
```

```
## S4 method for signature 'PFIMProject'
setModel(object, model)
```

Arguments

object	An object from the class PFIMProject .
model	An object from the class Model .

Value

The object with the updated model.

setModelError	<i>Set the model error.</i>
---------------	-----------------------------

Description

Set the model error.

Usage

```
setModelError(object, modelError)

## S4 method for signature 'Model'
setModelError(object, modelError)
```

Arguments

object	An object from the class Model .
modelError	An object from the class ModelError .

Value

The model with the updated model error.

setModelFromLibrary	<i>Set a model from the library of model</i>
---------------------	--

Description

Set a model from the library of model

Usage

```
setModelFromLibrary(object, modelFromLibrary)

## S4 method for signature 'Model'
setModelFromLibrary(object, modelFromLibrary)
```

Arguments

object	An object from the class Model .
modelFromLibrary	An object from the class Model .

Value

The model with the updated model from library of models.

setMu	<i>Set the value of the fixed effect mu of an object.</i>
-------	---

Description

Set the value of the fixed effect mu of an object.

Usage

```
setMu(object, value)

## S4 method for signature 'Distribution'
setMu(object, value)

## S4 method for signature 'ModelParameter'
setMu(object, value)
```

Arguments

object	An object defined form a class of PFIM.
value	The value of the fixed effect mu.

Value

The object with the updated fixed effect mu.

setName	<i>Set the name of an object.</i>
---------	-----------------------------------

Description

Set the name of an object.

Usage

```
setName(object, name)

## S4 method for signature 'Arm'
setName(object, name)

## S4 method for signature 'Design'
setName(object, name)

## S4 method for signature 'Model'
setName(object, name)
```


Arguments

object An object defined form a class of PFIM.
 name A string giving the name of the object.

Value

The object with the updated name.

setNumberOfArms *setNumberOfArms*

Description

Set the number of arms in a design.

Usage

```
setNumberOfArms(object, numberOfArms)

## S4 method for signature 'Design'
setNumberOfArms(object, numberOfArms)
```

Arguments

object An object Design from the class [Design](#).
 numberOfArms A numeric numberOfArms giving the new number of arms in the design.

Value

An object Design with the numberOfArms updated.

setOdeSolverParameters
 Set the parameters of the ode solver.

Description

Set the parameters of the ode solver.

Usage

```
setOdeSolverParameters(object, odeSolverParameters)

## S4 method for signature 'Model'
setOdeSolverParameters(object, odeSolverParameters)
```

Arguments

object An object from the class [Model](#).
odeSolverParameters A list giving the parameters of the ode solver.

Value

The model with the updated parameters of the ode solver.

setOmega	<i>Set the matrix omega of an object.</i>
----------	---

Description

Set the matrix omega of an object.

Usage

```
setOmega(object, value)

## S4 method for signature 'Distribution'
setOmega(object, value)

## S4 method for signature 'ModelParameter'
setOmega(object, value)
```

Arguments

object An object defined form a class of PFIM.
value The matrix omega.

Value

The object with the updated matrix omega.

setOptimalDesign	<i>Set the optimal design.</i>
------------------	--------------------------------

Description

Set the optimal design.

Usage

```
setOptimalDesign(object, optimalDesign)
```

```
## S4 method for signature 'OptimizationAlgorithm'  
setOptimalDesign(object, optimalDesign)
```

Arguments

object An object from the class [OptimizationAlgorithm](#).
optimalDesign An object from the class [Design](#).

Value

The object with the updated optimal design.

setOptimalWeights	<i>Set the optimal weights.</i>
-------------------	---------------------------------

Description

Set the optimal weights.

Usage

```
setOptimalWeights(object, optimalWeights)
```

```
## S4 method for signature 'MultiplicativeAlgorithm'  
setOptimalWeights(object, optimalWeights)
```

Arguments

object An object from the class [MultiplicativeAlgorithm](#).
optimalWeights A vector giving the optimal weights.

Value

The object with the updated optimal weights.

```
setOptimizationResults
    Set the optimization results.
```

Description

Set the optimization results.

Usage

```
setOptimizationResults(object, value)

## S4 method for signature 'Optimization'
setOptimizationResults(object, value)
```

Arguments

object An object from the class [Optimization](#).
value An object from the class [OptimizationAlgorithm](#) giving the optimization results.

Value

The object with the updated object from the class [OptimizationAlgorithm](#).

```
setOutcome            setOutcome
```

Description

Set the outcome of an object.

Usage

```
setOutcome(object, outcome)

## S4 method for signature 'Administration'
setOutcome(object, outcome)

## S4 method for signature 'SamplingTimes'
setOutcome(object, outcome)
```

Arguments

object An object defined form a class of PFIM.
outcome A string defined the outcome.

Value

A string giving the updated outcome of the object.

setOutcomes	<i>Set the outcomes of a model.</i>
-------------	-------------------------------------

Description

Set the outcomes of a model.

Usage

```
setOutcomes(object, outcomes)

## S4 method for signature 'Model'
setOutcomes(object, outcomes)
```

Arguments

object	An object from the class Model .
outcomes	A list giving the outcomes of the model.

Value

The model with the updated outcomes.

setOutcomesEvaluation	<i>setOutcomesEvaluation</i>
-----------------------	------------------------------

Description

Set the results of the evaluation of the outcomes.

Usage

```
setOutcomesEvaluation(object, outcomesEvaluation)

## S4 method for signature 'Design'
setOutcomesEvaluation(object, outcomesEvaluation)
```

Arguments

object	An object Design from the class Design .
outcomesEvaluation	A list containing the evaluation of the outcomes.

Value

An object Design with the list outcomesEvaluation updated.

```
setOutcomesForEvaluation
```

Set the outcomes of a model used for the evaluation (is scales outcomes).

Description

Set the outcomes of a model used for the evaluation (is scales outcomes).

Usage

```
setOutcomesForEvaluation(object, outcomes)
```

```
## S4 method for signature 'Model'
```

```
setOutcomesForEvaluation(object, outcomes)
```

Arguments

object An object from the class [Model](#).

outcomes A list giving the outcomes of a model used for the evaluation (is scales outcomes).

Value

The model with the updated outcomes for the evaluation.

```
setOutcomesGradient    setOutcomesGradient
```

Description

Set the results of the evaluation of the outcomes.

Usage

```
setOutcomesGradient(object, outcomesGradient)
```

```
## S4 method for signature 'Design'
```

```
setOutcomesGradient(object, outcomesGradient)
```

Arguments

object An object Design from the class [Design](#).
 outcomesGradient A list containing the evaluation of the outcome gradients.

Value

An object Design with the list outcomesGradient updated.

setParameters	<i>Set the parameters of an object.</i>
---------------	---

Description

Set the parameters of an object.

Usage

```
setParameters(object, parameters)

## S4 method for signature 'Distribution'
setParameters(object, parameters)

## S4 method for signature 'Model'
setParameters(object, parameters)

## S4 method for signature 'FedorovWynnAlgorithm'
setParameters(object, parameters)

## S4 method for signature 'MultiplicativeAlgorithm'
setParameters(object, parameters)

## S4 method for signature 'PGBAlgorithm'
setParameters(object, parameters)

## S4 method for signature 'PSOAlgorithm'
setParameters(object, parameters)

## S4 method for signature 'SimplexAlgorithm'
setParameters(object, parameters)
```

Arguments

object An object defined form a class of PFIM.
 parameters A list of parameters.

Value

The object with the updated list of parameters.

```
setSamplingConstraintForOptimization
    setSamplingConstraintForOptimization
```

Description

Set the sampling times constraint for optimization with PSO, PGBO and Simplex

Usage

```
setSamplingConstraintForOptimization(object)

## S4 method for signature 'Design'
setSamplingConstraintForOptimization(object)
```

Arguments

object An object from the class [Design](#).

Value

The arms with the sampling times constraints.

```
setSamplings            Set the sampling times.
```

Description

Set the sampling times.

Usage

```
setSamplings(object, samplings)

## S4 method for signature 'SamplingTimes'
setSamplings(object, samplings)
```

Arguments

object An object from the class [SamplingTimes](#).
 samplings A vector giving the sampling times.

Value

The updated sampling times.

setSamplingTime	<i>setSamplingTime</i>
-----------------	------------------------

Description

Set the sampling time of an arm.

Usage

```
setSamplingTime(object, samplingTime)
```

```
## S4 method for signature 'Arm'  
setSamplingTime(object, samplingTime)
```

Arguments

object An object Arm from the class [Arm](#).
samplingTime An object samplingTime from the class [SamplingTimes](#).

Value

An object Arm from the class [Arm](#) with the new sampling time samplingTime.

setSamplingTimes	<i>setSamplingTimes</i>
------------------	-------------------------

Description

Set the vectors of sampling times for an arm.

Usage

```
setSamplingTimes(object, samplingTimes)
```

```
## S4 method for signature 'Arm'  
setSamplingTimes(object, samplingTimes)
```

Arguments

object An object Arm from the class [Arm](#).
samplingTimes The list containing the new sampling times.

Value

An object Arm from the class [Arm](#) with the new sampling times samplingTimes.

```
setSamplingTimesConstraints
      setSamplingTimesConstraints
```

Description

Set the sampling times constraints.

Usage

```
setSamplingTimesConstraints(object, samplingTimesConstraints)

## S4 method for signature 'Arm'
setSamplingTimesConstraints(object, samplingTimesConstraints)
```

Arguments

`object` An object `Arm` from the class [Arm](#).
`samplingTimesConstraints` An object `SamplingTimeConstraints` from the class [SamplingTimeConstraints](#).

Value

The arm with the new sampling time constraints.

```
setShrinkage      Set the shrinkage.
```

Description

Set the shrinkage.

Usage

```
setShrinkage(object, value)

## S4 method for signature 'BayesianFim'
setShrinkage(object, value)

## S4 method for signature 'IndividualFim'
setShrinkage(object, value)

## S4 method for signature 'PopulationFim'
setShrinkage(object, value)
```

Arguments

object	An object from the class Fim .
value	A vector giving the shrinkage of the Bayesian fim.

Value

The object with the updated shrinkage.

setSigmaInter	<i>Set the parameter sigma inter.</i>
---------------	---------------------------------------

Description

Set the parameter sigma inter.

Usage

```
setSigmaInter(object, sigmaInter)

## S4 method for signature 'ModelError'
setSigmaInter(object, sigmaInter)
```

Arguments

object	An object from the class ModelError .
sigmaInter	A numeric giving the parameter sigma inter.

Value

The model error with the updated sigma inter.

setSigmaSlope	<i>Set the parameter sigma slope.</i>
---------------	---------------------------------------

Description

Set the parameter sigma slope.

Usage

```
setSigmaSlope(object, sigmaSlope)

## S4 method for signature 'ModelError'
setSigmaSlope(object, sigmaSlope)
```

Arguments

object	An object from the class ModelError .
sigmaSlope	A numeric giving the parameter sigma slope.

Value

The model error with the updated sigma slope.

setSize	<i>setSize</i>
---------	----------------

Description

Set the size of an object.

Set the size of an arm.

Usage

```
setSize(object, size)
```

```
setSize(object, size)
```

```
## S4 method for signature 'Arm'
setSize(object, size)
```

```
## S4 method for signature 'Design'
setSize(object, size)
```

Arguments

object	An object Arm from the class Arm .
size	A numeric giving the new size of the object Arm.

Value

The object with its size updated.

The object Arm object with its new size.

setTau	<i>setTau</i>
--------	---------------

Description

Set the frequency tau.

Usage

```
setTau(object, tau)
```

```
## S4 method for signature 'Administration'  
setTau(object, tau)
```

Arguments

object	An object Administration from the class Administration .
tau	A numeric value for the infusion lag tau.

Value

The object Administration object with its new value of the infusion lag tau.

setTimeDose	<i>setTimeDose</i>
-------------	--------------------

Description

Set the times vector when doses are given.

Usage

```
setTimeDose(object, timeDose)
```

```
## S4 method for signature 'Administration'  
setTimeDose(object, timeDose)
```

Arguments

object	An object Administration from the class Administration .
timeDose	A numeric value of the time dose.

Value

The object Administration with its new times vector for doses.

setTinf	<i>Set the infusion duration.</i>
---------	-----------------------------------

Description

Set the infusion duration.

Usage

```
setTinf(object, Tinf)
```

```
## S4 method for signature 'Administration'  
setTinf(object, Tinf)
```

Arguments

object	An object Administration from the class Administration .
Tinf	A numeric value for the infusion duration Tinf.

Value

The object Administration with its new value of the infusion duration Tinf.

setVarianceEffects	<i>Set the matrix of the variance effects.</i>
--------------------	--

Description

Set the matrix of the variance effects.

Usage

```
setVarianceEffects(object)
```

```
## S4 method for signature 'Fim'  
setVarianceEffects(object)
```

Arguments

object	An object from the class Fim .
--------	--

Value

Update the matrix of the variance effects.

show,Design-method *show*

Description

show
show
show
show
show
show
show
show

Usage

```
## S4 method for signature 'Design'  
show(object)  
  
## S4 method for signature 'Evaluation'  
show(object)  
  
## S4 method for signature 'FedorovWynnAlgorithm'  
show(object)  
  
## S4 method for signature 'MultiplicativeAlgorithm'  
show(object)  
  
## S4 method for signature 'Optimization'  
show(object)  
  
## S4 method for signature 'PGBAlgorithm'  
show(object)  
  
## S4 method for signature 'PSOAlgorithm'  
show(object)  
  
## S4 method for signature 'SimplexAlgorithm'  
show(object)
```

Arguments

object object

SimplexAlgorithm-class

Class "SimplexAlgorithm"

Description

Class "SimplexAlgorithm" implements the Multiplicative algorithm.

Objects from the class SimplexAlgorithm

Objects from the class SimplexAlgorithm can be created by calls of the form SimplexAlgorithm(...) where (...) are the parameters for the SimplexAlgorithm objects.

Slots for SimplexAlgorithm objects

pctInitialSimplexBuilding: A numeric giving the percentage of the initial simplex.

maxIteration: A numeric giving the number of maximum iteration.

tolerance: A numeric giving the tolerance threshold.

showProcess: A boolean to show or not the process.

optimalDesign: A Design object giving the optimal design.

iterationAndCriteria: A list giving the optimal criteria at each iteration.

Index

- addModel, [14, 21](#)
- addModel, LibraryOfModels-method
(addModel), [21](#)
- addModels, [14, 21](#)
- addModels, LibraryOfModels-method
(addModels), [21](#)
- Administration, [9, 60, 96, 97, 159, 181, 182](#)
- Administration (Administration-class),
[22](#)
- Administration-class, [22](#)
- AdministrationConstraints, [10](#)
- AdministrationConstraints
(AdministrationConstraints-class),
[22](#)
- AdministrationConstraints-class, [22](#)
- Arm, [10, 24, 34, 36–40, 49–51, 56, 68, 91–93,](#)
[153, 155, 156, 177, 178, 180](#)
- Arm (Arm-class), [23](#)
- Arm-class, [23](#)
- BayesianFim, [10](#)
- BayesianFim (BayesianFim-class), [23](#)
- BayesianFim-class, [23](#)
- checkSamplingTimeConstraintsForContinuousOptimization, [19, 23](#)
- checkSamplingTimeConstraintsForContinuousOptimization, Design-method
(checkSamplingTimeConstraintsForContinuousOptimization),
[23](#)
- checkValiditySamplingConstraint, [24](#)
- checkValiditySamplingConstraint, Design-method
(checkValiditySamplingConstraint),
[24](#)
- Combined1, [11, 145](#)
- Combined1 (Combined1-class), [25](#)
- Combined1-class, [25](#)
- computeVMat, [19, 25](#)
- Constant, [11](#)
- Constant (Constant-class), [26](#)
- Constant-class, [26](#)
- convertPKModelAnalyticToPKModelODE, [14,](#)
[15, 26](#)
- convertPKModelAnalyticToPKModelODE, ModelAnalytic-method
(convertPKModelAnalyticToPKModelODE),
[26](#)
- convertPKModelAnalyticToPKModelODE, ModelAnalyticInfusion-method
(convertPKModelAnalyticToPKModelODE),
[26](#)
- convertPKModelAnalyticToPKModelODE, ModelAnalyticSteadyState-method
(convertPKModelAnalyticToPKModelODE),
[26](#)
- dataForArmEvaluation, [27](#)
- dataForArmEvaluation, Design-method
(dataForArmEvaluation), [27](#)
- defineModel, [15, 27](#)
- defineModel, Model-method (defineModel),
[27](#)
- defineModelEquationsFromStringToFunction,
[28](#)
- defineModelEquationsFromStringToFunction, ModelAnalytic-method
(defineModelEquationsFromStringToFunction),
[28](#)
- defineModelEquationsFromStringToFunction, ModelAnalyticInfusion-method
(defineModelEquationsFromStringToFunction),
[28](#)
- defineModelEquationsFromStringToFunction, ModelAnalyticSteadyState-method
(defineModelEquationsFromStringToFunction),
[28](#)
- defineModelEquationsFromStringToFunction, ModelODEBolus-method
(defineModelEquationsFromStringToFunction),
[28](#)
- defineModelEquationsFromStringToFunction, ModelODEDoseInEquation-method
(defineModelEquationsFromStringToFunction),
[28](#)
- defineModelEquationsFromStringToFunction, ModelODEDoseNotInEquation-method
(defineModelEquationsFromStringToFunction),
[28](#)

- 28
- defineModelEquationsFromStringToFunction, ModelODEInfusionDosePKModel-method
(defineModelEquationsFromStringToFunction), 32
- defineModelFromLibraryOfModels, 15, 30
- defineModelFromLibraryOfModels, Model-method
(defineModelFromLibraryOfModels), 30
- defineModelType, 15, 30
- defineModelType, Model-method
(defineModelType), 30
- defineModelUserDefined, 15, 31
- defineModelUserDefined, Model-method
(defineModelUserDefined), 31
- definePKModel, 15–17, 31
- definePKModel, ModelAnalytic-method
(definePKModel), 31
- definePKModel, ModelAnalyticInfusion-method
(definePKModel), 31
- definePKModel, ModelAnalyticSteadyState-method
(definePKModel), 31
- definePKModel, ModelODE-method
(definePKModel), 31
- definePKModel, ModelODEDoseInEquations-method
(definePKModel), 31
- definePKModel, ModelODEInfusionDoseInEquations-method
(definePKModel), 31
- definePKPDMModel, 15–17, 32
- definePKPDMModel, ModelAnalytic, ModelAnalytic-method
(definePKPDMModel), 32
- definePKPDMModel, ModelAnalytic, ModelODE-method
(definePKPDMModel), 32
- definePKPDMModel, ModelAnalyticInfusion, ModelAnalytic-method
(definePKPDMModel), 32
- definePKPDMModel, ModelAnalyticInfusion, ModelODE-method
(definePKPDMModel), 32
- definePKPDMModel, ModelAnalyticSteadyState, ModelAnalyticSteadyState-method
(definePKPDMModel), 32
- definePKPDMModel, ModelAnalyticSteadyState, ModelODE-method
(definePKPDMModel), 32
- definePKPDMModel, ModelODEBolus, ModelODE-method
(definePKPDMModel), 32
- definePKPDMModel, ModelODEDoseInEquations, ModelODE-method
(definePKPDMModel), 32
- definePKPDMModel, ModelODEDoseNotInEquations, ModelODE-method
(definePKPDMModel), 32
- definePKPDMModel, ModelODEInfusion, ModelODE-method
(definePKPDMModel), 32
- definePKPDMModel, ModelODEInfusionDoseInEquations, ModelODE-method
(definePKPDMModel), 32
- Design (Design-class), 33
- Design-class, 33
- Distribution, 11, 49, 158
- Distribution (Distribution-class), 34
- Distribution-class, 34
- EvaluateArm, 10, 34
- EvaluateArm, Arm-method (EvaluateArm), 34
- EvaluateDesign, 11, 35
- EvaluateDesign, Design-method
(EvaluateDesign), 35
- EvaluateErrorModelDerivatives, 16, 35
- EvaluateErrorModelDerivatives, ModelError-method
(EvaluateErrorModelDerivatives), 35
- EvaluateFisherMatrix, 10, 12, 13, 19, 36
- EvaluateFisherMatrix, BayesianFim-method
(EvaluateFisherMatrix), 36
- EvaluateFisherMatrix, IndividualFim-method
(EvaluateFisherMatrix), 36
- EvaluateFisherMatrix, PopulationFim-method
(EvaluateFisherMatrix), 36
- EvaluateModel, 15–17, 37
- EvaluateModel, ModelAnalytic-method
(EvaluateModel), 37
- EvaluateModel, ModelAnalyticInfusion-method
(EvaluateModel), 37
- EvaluateModel, ModelAnalyticInfusionSteadyState-method
(EvaluateModel), 37
- EvaluateModel, ModelAnalyticSteadyState-method
(EvaluateModel), 37
- EvaluateModel, ModelODEBolus-method
(EvaluateModel), 37
- EvaluateModel, ModelODEDoseInEquations-method
(EvaluateModel), 37
- EvaluateModel, ModelODEDoseNotInEquations-method
(EvaluateModel), 37
- EvaluateModel, ModelODEInfusionDoseInEquations-method
(EvaluateModel), 37
- EvaluateModelGradient, 38
- EvaluateModelGradient, ModelAnalytic-method
(EvaluateModelGradient), 38
- EvaluateModelGradient, ModelAnalyticInfusion-method
(EvaluateModelGradient), 38

- EvaluateModelGradient, ModelAnalyticInfusionSteadyStateReportEvaluation, PopulationFim-method (EvaluateModelGradient), 38 (generateReportEvaluation), 44
- EvaluateModelGradient, ModelAnalyticSteadyStateReportOptimization, 12, 17–19, 46 (EvaluateModelGradient), 38
- EvaluateModelGradient, ModelODEBolus-method generateReportOptimization, FedorovWynnAlgorithm-method (EvaluateModelGradient), 38 (generateReportOptimization),
- EvaluateModelGradient, ModelODEDoseInEquations-method 46 (EvaluateModelGradient), 38 generateReportOptimization, MultiplicativeAlgorithm-method
- EvaluateModelGradient, ModelODEDoseNotInEquations-method (generateReportOptimization), 46 (EvaluateModelGradient), 38
- EvaluateModelGradient, ModelODEInfusionDoseInEquationsReportOptimization, PGBAlgorithm-method (EvaluateModelGradient), 38 (generateReportOptimization),
- EvaluateVarianceFIM, 12, 13, 19, 39 46
- EvaluateVarianceFIM, IndividualFim-method generateReportOptimization, PSOAlgorithm-method (EvaluateVarianceFIM), 39 (generateReportOptimization),
- EvaluateVarianceFIM, PopulationFim-method 46 (EvaluateVarianceFIM), 39
- EvaluateVarianceModel, 15, 39 generateReportOptimization, SimplexAlgorithm-method (generateReportOptimization),
- EvaluateVarianceModel, Model-method 46 (EvaluateVarianceModel), 39
- Evaluation, 11, 64, 140, 143, 144, 150, 161, generateSamplingsFromSamplingConstraints, 19, 47 162
- Evaluation (Evaluation-class), 40 generateSamplingsFromSamplingConstraints, SamplingTimeConst (generateSamplingsFromSamplingConstraints),
- Evaluation-class, 40 47
- FedorovWynnAlgorithm, 12, 81 generateTables, 12, 18, 48
- FedorovWynnAlgorithm generateTables, Evaluation-method (FedorovWynnAlgorithm-class), (generateTables), 48
- 41 generateTables, Optimization-method (generateTables), 48
- FedorovWynnAlgorithm-class, 41
- FedorovWynnAlgorithm_Rcpp, 12, 41
- Fim, 12, 34–36, 39, 44, 45, 52–55, 57, 59, 61, getAdjustedGradient, 11, 14, 17, 48 66, 90, 93, 94, 98, 148, 162–164, 179, 182
- getAdjustedGradient, LogNormal-method (getAdjustedGradient), 48
- getAdjustedGradient, Normal-method (getAdjustedGradient), 48
- Fim (Fim-class), 42
- Fim-class, 42
- fisher.simplex, 19, 43
- fun.amoeba, 19, 43
- generateFimsFromConstraints, 18, 44
- generateFimsFromConstraints, Optimization-method 49 (generateFimsFromConstraints),
- 44
- generateReportEvaluation, 11, 13, 19, 44
- generateReportEvaluation, BayesianFim-method (generateReportEvaluation), 44
- generateReportEvaluation, IndividualFim-method (generateReportEvaluation), 44
- generateReportEvaluation, PopulationFim-method (generateReportEvaluation), 44
- generateReportOptimization, FedorovWynnAlgorithm-method (generateReportOptimization),
- generateReportOptimization, MultiplicativeAlgorithm-method (generateReportOptimization),
- generateReportOptimization, PGBAlgorithm-method (generateReportOptimization),
- generateReportOptimization, PSOAlgorithm-method (generateReportOptimization),
- generateReportOptimization, SimplexAlgorithm-method (generateReportOptimization),
- generateSamplingsFromSamplingConstraints, 19, 47
- generateSamplingsFromSamplingConstraints, SamplingTimeConst (generateSamplingsFromSamplingConstraints),
- 47
- generateTables, 12, 18, 48
- generateTables, Evaluation-method (generateTables), 48
- generateTables, Optimization-method (generateTables), 48
- getAdjustedGradient, 11, 14, 17, 48
- getAdjustedGradient, LogNormal-method (getAdjustedGradient), 48
- getAdjustedGradient, Normal-method (getAdjustedGradient), 48
- getAdministration, 10, 49
- getAdministration, Arm-method (getAdministration), 49
- getAdministrationConstraint, 10, 49
- getAdministrationConstraint, Arm-method (getAdministrationConstraint),
- 49
- getAdministrations, 10, 50
- getAdministrations, Arm-method (getAdministrations), 50
- getAdministrationsConstraints, 10, 50
- getAdministrationsConstraints, Arm-method (getAdministrationsConstraints),
- 50

- getArms, [13](#), [51](#)
- getArms, Design-method (getArms), [51](#)
- getArms, OptimizationAlgorithm-method (getArms), [51](#)
- getcError, [16](#), [51](#)
- getcError, ModelError-method (getcError), [51](#)
- getColumnAndParametersNamesFIM, [12](#), [52](#)
- getColumnAndParametersNamesFIM, BayesianFim-method (getColumnAndParametersNamesFIM), [52](#)
- getColumnAndParametersNamesFIM, IndividualFim-method (getColumnAndParametersNamesFIM), [52](#)
- getColumnAndParametersNamesFIM, PopulationFim-method (getColumnAndParametersNamesFIM), [52](#)
- getColumnAndParametersNamesFIMInLatex, [13](#), [53](#)
- getColumnAndParametersNamesFIMInLatex, BayesianFim-method (getColumnAndParametersNamesFIMInLatex), [53](#)
- getColumnAndParametersNamesFIMInLatex, IndividualFim-method (getColumnAndParametersNamesFIMInLatex), [53](#)
- getColumnAndParametersNamesFIMInLatex, PopulationFim-method (getColumnAndParametersNamesFIMInLatex), [53](#)
- getConditionNumberFixedEffects, [12](#), [53](#)
- getConditionNumberFixedEffects, Fim-method (getConditionNumberFixedEffects), [53](#)
- getConditionNumberVarianceEffects, [10](#), [12](#), [54](#)
- getConditionNumberVarianceEffects, BayesianFim-method (getConditionNumberVarianceEffects), [54](#)
- getConditionNumberVarianceEffects, Fim-method (getConditionNumberVarianceEffects), [54](#)
- getContent, [14](#), [54](#)
- getContent, LibraryOfModels-method (getContent), [54](#)
- getCorrelationMatrix, [12](#), [55](#)
- getCorrelationMatrix, Evaluation-method (getCorrelationMatrix), [55](#)
- getCorrelationMatrix, Fim-method (getCorrelationMatrix), [55](#)
- getCorrelationMatrix, Optimization-method (getCorrelationMatrix), [55](#)
- getDataForArmEvaluation, [55](#)
- getDataForArmEvaluation, Arm-method (getDataForArmEvaluation), [55](#)
- getDataFrameResults, [17](#), [56](#)
- getDataFrameResults, FedorovWynnAlgorithm-method (getDataFrameResults), [56](#)
- getDataFrameResults, MultiplicativeAlgorithm-method (getDataFrameResults), [56](#)
- getDataFrameResults, Optimization-method (getDataFrameResults), [56](#)
- getDcriterion, [12](#), [57](#)
- getDcriterion, Evaluation-method (getDcriterion), [57](#)
- getDcriterion, Fim-method (getDcriterion), [57](#)
- getDcriterion, Optimization-method (getDcriterion), [57](#)
- getDelta, [14](#), [57](#)
- getDelta, MultiplicativeAlgorithm-method (getDelta), [57](#)
- getDerivatives, [16](#), [58](#)
- getDerivatives, ModelError-method (getDerivatives), [58](#)
- getDescription, [14](#), [58](#)
- getDescription, Model-method (getDescription), [58](#)
- getDesigns, [18](#), [59](#)
- getDesigns, PFIMProject-method (getDesigns), [59](#)
- getDeterminant, [12](#), [59](#)
- getDeterminant, Evaluation-method (getDeterminant), [59](#)
- getDeterminant, Fim-method (getDeterminant), [59](#)
- getDeterminant, Optimization-method (getDeterminant), [59](#)
- getDistribution, [17](#), [60](#)
- getDistribution, ModelParameter-method (getDistribution), [60](#)
- getDose, [9](#), [10](#), [60](#)
- getDose, Administration-method (getDose), [60](#)
- getDose, AdministrationConstraints-method (getDose), [60](#)
- getEigenValues, [12](#), [61](#)
- getEigenValues, Fim-method

- (getEigenValues), 61
- getElementaryProtocols, 18, 61
- getElementaryProtocols, Optimization-method (getElementaryProtocols), 61
- getEquation, 15, 62
- getEquation, ModelError-method (getEquation), 62
- getEquations, 14, 62
- getEquations, Model-method (getEquations), 62
- getEquationsAfterInfusion, 16, 63
- getEquationsAfterInfusion, Model-method (getEquationsAfterInfusion), 63
- getEquationsDuringInfusion, 16, 63
- getEquationsDuringInfusion, Model-method (getEquationsDuringInfusion), 63
- getEvaluationFIMResults, 18, 64
- getEvaluationFIMResults, Optimization-method (getEvaluationFIMResults), 64
- getEvaluationInitialDesignResults, 18, 64
- getEvaluationInitialDesignResults, Optimization-method (getEvaluationInitialDesignResults), 64
- getFim, 11, 13, 18, 65
- getFim, Design-method (getFim), 65
- getFim, OptimizationAlgorithm-method (getFim), 65
- getFim, PFIMProject-method (getFim), 65
- getFisherMatrix, 12, 65
- getFisherMatrix, Evaluation-method (getFisherMatrix), 65
- getFisherMatrix, Fim-method (getFisherMatrix), 65
- getFisherMatrix, Optimization-method (getFisherMatrix), 65
- getFixedEffects, 12, 66
- getFixedEffects, Fim-method (getFixedEffects), 66
- getFixedMu, 17, 66
- getFixedMu, ModelParameter-method (getFixedMu), 66
- getFixedOmega, 17, 67
- getFixedOmega, ModelParameter-method (getFixedOmega), 67
- getFixedParameters, 15, 67
- getFixedParameters, Model-method (getFixedParameters), 67
- getFixedTimes, 19, 68
- getFixedTimes, SamplingTimeConstraints-method (getFixedTimes), 68
- getInitialConditions, 10, 14, 68
- getInitialConditions, Arm-method (getInitialConditions), 68
- getInitialConditions, Model-method (getInitialConditions), 68
- getIterationAndCriteria, 69
- getIterationAndCriteria, OptimizationAlgorithm-method (getIterationAndCriteria), 69
- getLambda, 17, 69
- getLambda, MultiplicativeAlgorithm-method (getLambda), 69
- getLibraryPDMModels, 14, 70
- getLibraryPDMModels, LibraryOfModels-method (getLibraryPDMModels), 70
- getLibraryPKModels, 14, 70
- getLibraryPKModels, LibraryOfModels-method (getLibraryPKModels), 70
- getMinSampling, 19, 71
- getMinSampling, SamplingTimeConstraints-method (getMinSampling), 71
- getModel, 18, 71
- getModel, PFIMProject-method (getModel), 71
- getModelEquations, 18, 72
- getModelEquations, PFIMProject-method (getModelEquations), 72
- getModelError, 13, 14, 18, 72
- getModelError, Model-method (getModelError), 72
- getModelError, PFIMProject-method (getModelError), 72
- getModelErrorParametersValues, 15, 73
- getModelErrorParametersValues, Model-method (getModelErrorParametersValues), 73
- getModelFromLibrary, 14, 73
- getModelFromLibrary, Model-method (getModelFromLibrary), 73
- getModelParameters, 18, 74
- getModelParameters, PFIMProject-method (getModelParameters), 74
- getModelParametersValues, 74
- getModelParametersValues, Model-method (getModelParametersValues), 74

- getMu, [11, 13, 17, 75](#)
- getMu, Distribution-method (getMu), [75](#)
- getMu, ModelParameter-method (getMu), [75](#)
- getName, [10, 11, 13, 14, 17, 18, 75](#)
- getName, Arm-method (getName), [75](#)
- getName, Design-method (getName), [75](#)
- getName, LibraryOfModels-method (getName), [75](#)
- getName, Model-method (getName), [75](#)
- getName, ModelParameter-method (getName), [75](#)
- getName, PFIMProject-method (getName), [75](#)
- getNames, [13, 76](#)
- getNames, list-method (getNames), [76](#)
- getNumberOfArms, [11, 77](#)
- getNumberOfArms, Design-method (getNumberOfArms), [77](#)
- getNumberOfIterations, [17, 77](#)
- getNumberOfIterations, MultiplicativeAlgorithm-method (getNumberOfIterations), [77](#)
- getNumberOfParameters, [14, 78](#)
- getNumberOfParameters, Model-method (getNumberOfParameters), [78](#)
- getNumberOfSamplingsOptimisable, [19, 78](#)
- getNumberOfSamplingsOptimisable, SamplingTimeConstraints-method (getNumberOfSamplingsOptimisable), [78](#)
- getNumberOfTimesByWindows, [19, 79](#)
- getNumberOfTimesByWindows, SamplingTimeConstraints-method (getNumberOfTimesByWindows), [79](#)
- getOdeSolverParameters, [13, 14, 18, 79](#)
- getOdeSolverParameters, Model-method (getOdeSolverParameters), [79](#)
- getOdeSolverParameters, PFIMProject-method (getOdeSolverParameters), [79](#)
- getOmega, [11, 13, 17, 80](#)
- getOmega, Distribution-method (getOmega), [80](#)
- getOmega, ModelParameter-method (getOmega), [80](#)
- getOptimalDesign, [80](#)
- getOptimalDesign, OptimizationAlgorithm-method (getOptimalDesign), [80](#)
- getOptimalFrequencies, [81](#)
- getOptimalFrequencies, FedorovWynnAlgorithm-method (getOptimalFrequencies), [81](#)
- getOptimalWeights, [17, 81](#)
- getOptimalWeights, MultiplicativeAlgorithm-method (getOptimalWeights), [81](#)
- getOptimizationResults, [17, 82](#)
- getOptimizationResults, Optimization-method (getOptimizationResults), [82](#)
- getOptimizer, [18, 82](#)
- getOptimizer, PFIMProject-method (getOptimizer), [82](#)
- getOptimizerParameters, [18, 83](#)
- getOptimizerParameters, PFIMProject-method (getOptimizerParameters), [83](#)
- getOutcome, [9, 10, 13, 15, 19, 83](#)
- getOutcome, Administration-method (getOutcome), [83](#)
- getOutcome, AdministrationConstraints-method (getOutcome), [83](#)
- getOutcome, ModelError-method (getOutcome), [83](#)
- getOutcome, SamplingTimeConstraints-method (getOutcome), [83](#)
- getOutcome, SamplingTimes-method (getOutcome), [83](#)
- getOutcomes, [14, 18, 84](#)
- getOutcomes, Model-method (getOutcomes), [84](#)
- getOutcomes, PFIMProject-method (getOutcomes), [84](#)
- getOutcomesEvaluation, [11, 84](#)
- getOutcomesEvaluation, Design-method (getOutcomesEvaluation), [84](#)
- getOutcomesForEvaluation, [14, 85](#)
- getOutcomesForEvaluation, Model-method (getOutcomesForEvaluation), [85](#)
- getOutcomesGradient, [11, 85](#)
- getOutcomesGradient, Design-method (getOutcomesGradient), [85](#)
- getParameters, [11, 13, 14, 16, 86](#)
- getParameters, Distribution-method (getParameters), [86](#)
- getParameters, Model-method (getParameters), [86](#)
- getParameters, ModelError-method (getParameters), [86](#)
- getPDModel, [14, 87](#)
- getPDModel, LibraryOfPKPModels-method (getPDModel), [87](#)
- getPKModel, [14, 87](#)
- getPKModel, LibraryOfPKPModels-method (getPKModel), [87](#)

- getPKPDMoDel, [14, 88](#)
- getPKPDMoDel, LibraryOfPKPDMoDels-method (getPKPDMoDel), [88](#)
- getPlotOptions, [88](#)
- getProportionsOfSubjects, [17, 89](#)
- getProportionsOfSubjects, Optimization-method (getProportionsOfSubjects), [89](#)
- getRSE, [10, 12, 13, 19, 89](#)
- getRSE, BayesianFim-method (getRSE), [89](#)
- getRSE, Evaluation-method (getRSE), [89](#)
- getRSE, IndividualFim-method (getRSE), [89](#)
- getRSE, Optimization-method (getRSE), [89](#)
- getRSE, PopulationFim-method (getRSE), [89](#)
- getSamplings, [13, 19, 90](#)
- getSamplings, SamplingTimeConstraints-method (getSamplings), [90](#)
- getSamplings, SamplingTimes-method (getSamplings), [90](#)
- getSamplingsWindows, [19, 90](#)
- getSamplingsWindows, SamplingTimeConstraints-method (getSamplingsWindows), [90](#)
- getSamplingTime, [10, 91](#)
- getSamplingTime, Arm-method (getSamplingTime), [91](#)
- getSamplingTimeConstraint, [10, 91](#)
- getSamplingTimeConstraint, Arm-method (getSamplingTimeConstraint), [91](#)
- getSamplingTimes, [10, 92](#)
- getSamplingTimes, Arm-method (getSamplingTimes), [92](#)
- getSamplingTimesConstraints, [10, 92](#)
- getSamplingTimesConstraints, Arm-method (getSamplingTimesConstraints), [92](#)
- getSE, [12, 93](#)
- getSE, Evaluation-method (getSE), [93](#)
- getSE, Fim-method (getSE), [93](#)
- getSE, Optimization-method (getSE), [93](#)
- getShrinkage, [10, 12, 13, 19, 93](#)
- getShrinkage, BayesianFim-method (getShrinkage), [93](#)
- getShrinkage, Evaluation-method (getShrinkage), [93](#)
- getShrinkage, IndividualFim-method (getShrinkage), [93](#)
- getShrinkage, Optimization-method (getShrinkage), [93](#)
- getShrinkage, PopulationFim-method (getShrinkage), [93](#)
- getSigmaInter, [16, 94](#)
- getSigmaInter, ModelError-method (getSigmaInter), [94](#)
- getSigmaSlope, [16, 95](#)
- getSigmaSlope, ModelError-method (getSigmaSlope), [95](#)
- getSize, [10, 11, 13, 95](#)
- getSize, Arm-method (getSize), [95](#)
- getSize, Design-method (getSize), [95](#)
- getTau, [10, 96](#)
- getTau, Administration-method (getTau), [96](#)
- getTimeDose, [9, 96](#)
- getTimeDose, Administration-method (getTimeDose), [96](#)
- getTinf, [10, 97](#)
- getTinf, Administration-method (getTinf), [97](#)
- getVariables, [97](#)
- getVariables, ModelInfusion-method (getVariables), [97](#)
- getVariables, ModelODE-method (getVariables), [97](#)
- getVariables, ModelODEBolus-method (getVariables), [97](#)
- getVarianceEffects, [12, 98](#)
- getVarianceEffects, Fim-method (getVarianceEffects), [98](#)
- getWeightThreshold, [17, 98](#)
- getWeightThreshold, MultiplicativeAlgorithm-method (getWeightThreshold), [98](#)
- IndividualFim, [13](#)
- IndividualFim (IndividualFim-class), [99](#)
- IndividualFim-class, [99](#)
- initialize, Administration-method, [99](#)
- initialize, AdministrationConstraints-method, [100](#)
- initialize, Arm-method, [100](#)
- initialize, Combined1-method, [101](#)
- initialize, Constant-method, [102](#)
- initialize, Design-method, [103](#)
- initialize, Distribution-method, [104](#)
- initialize, Evaluation-method, [104](#)
- initialize, FedorovWynnAlgorithm-method, [105](#)
- initialize, Fim-method, [106](#)
- initialize, LibraryOfModels-method, [106](#)

- initialize,LibraryOfPKPDMODELS-method, 107
- initialize,LogNormal-method, 107
- initialize,Model-method, 108
- initialize,ModelAnalytic-method, 109
- initialize,ModelAnalyticBolus-method, 109
- initialize,ModelAnalyticBolusSteadyState-method, 110
- initialize,ModelAnalyticInfusion-method, 111
- initialize,ModelAnalyticInfusionSteadyState-method, 112
- initialize,ModelAnalyticSteadyState-method, 113
- initialize,ModelBolus-method, 113
- initialize,ModelError-method, 114
- initialize,ModelInfusion-method, 115
- initialize,ModelParameter-method, 116
- initialize,MultiplicativeAlgorithm-method, 117
- initialize,Normal-method, 118
- initialize,Optimization-method, 118
- initialize,OptimizationAlgorithm-method, 119
- initialize,PFIMProject-method, 120
- initialize,PGBOAlgorithm-method, 120
- initialize,Proportional-method, 121
- initialize,PSOAlgorithm-method, 122
- initialize,SamplingTimeConstraints-method, 123
- initialize,SamplingTimes-method, 124
- initialize,SimplexAlgorithm-method, 125
- isDoseInEquations, 15, 126
- isDoseInEquations,Model-method (isDoseInEquations), 126
- isModelAnalytic, 15, 126
- isModelAnalytic,Model-method (isModelAnalytic), 126
- isModelBolus, 15, 127
- isModelBolus,Model-method (isModelBolus), 127
- isModelInfusion, 15, 127
- isModelInfusion,Model-method (isModelInfusion), 127
- isModelODE, 15, 128
- isModelODE,Model-method (isModelODE), 128
- isModelSteadyState, 15, 128
- isModelSteadyState,Model-method (isModelSteadyState), 128
- LibraryOfModels, 13, 21, 55, 70, 155
- LibraryOfModels (LibraryOfModels-class), 129
- LibraryOfModels-class, 129
- LibraryOfPDMODELS, 129
- LibraryOfPKMODELS, 129
- LibraryOfPKPDMODELS, 14, 87, 88
- LibraryOfPKPDMODELS (LibraryOfPKPDMODELS-class), 130
- LibraryOfPKPDMODELS-class, 130
- LogNormal, 14
- LogNormal (LogNormal-class), 130
- LogNormal-class, 130
- Model, 14–16, 21, 26, 27, 29–40, 52, 53, 58, 62, 63, 67, 73, 74, 78, 84, 85, 90, 97, 126–128, 138, 142, 149, 156, 157, 160, 161, 165–167, 170, 173, 174
- Model (Model-class), 130
- Model-class, 130
- ModelAnalytic, 15
- ModelAnalytic (ModelAnalytic-class), 131
- ModelAnalytic-class, 131
- ModelAnalyticBolus, 15
- ModelAnalyticBolus (ModelAnalyticBolus-class), 131
- ModelAnalyticBolus-class, 131
- ModelAnalyticBolusSteadyState, 15
- ModelAnalyticBolusSteadyState (ModelAnalyticBolusSteadyState-class), 131
- ModelAnalyticBolusSteadyState-class, 131
- ModelAnalyticInfusion (ModelAnalyticInfusion-class), 131
- ModelAnalyticInfusion-class, 131
- ModelAnalyticInfusionSteadyState (ModelAnalyticInfusionSteadyState-class), 132
- ModelAnalyticInfusionSteadyState-class, 132

- ModelAnalyticSteadyState
 - (ModelAnalyticSteadyState-class), 132
- ModelAnalyticSteadyState-class, 132
- ModelBolus, 15
- ModelBolus (ModelBolus-class), 132
- ModelBolus-class, 132
- ModelError, 11, 15, 19, 25, 26, 35, 52, 58, 62, 94, 95, 154, 157, 159, 167, 179, 180
- ModelError (ModelError-class), 132
- ModelError-class, 132
- ModelInfusion, 16
- ModelInfusion (ModelInfusion-class), 132
- ModelInfusion-class, 132
- ModelODE, 16
- ModelODE (ModelODE-class), 133
- ModelODE-class, 133
- ModelODEBolus, 16
- ModelODEBolus (getVariables), 97
- ModelODEBolus-class (getVariables), 97
- ModelODEDoseInEquations, 16
- ModelODEDoseInEquations
 - (ModelODEDoseInEquations-class), 133
- ModelODEDoseInEquations-class, 133
- ModelODEDoseNotInEquations, 16
- ModelODEDoseNotInEquations
 - (ModelODEDoseNotInEquations-class), 133
- ModelODEDoseNotInEquations-class, 133
- ModelODEInfusion, 16
- ModelODEInfusion
 - (ModelODEInfusion-class), 133
- ModelODEInfusion-class, 133
- ModelODEInfusionDoseInEquations, 16
- ModelODEInfusionDoseInEquations
 - (ModelODEInfusionDoseInEquations-class), 134
- ModelODEInfusionDoseInEquations-class, 134
- ModelParameter, 17, 60, 66, 67, 158, 164, 165
- ModelParameter (ModelParameter-class), 134
- ModelParameter-class, 134
- MultiplicativeAlgorithm, 17, 57, 69, 77, 81, 98, 171
- MultiplicativeAlgorithm
 - (MultiplicativeAlgorithm-class), 134
- MultiplicativeAlgorithm-class, 134
- MultiplicativeAlgorithm_Rcpp, 17, 135
- Normal, 17
- Normal (Normal-class), 136
- Normal-class, 136
- Optimization, 17, 43, 44, 47, 61, 64, 82, 89, 158, 161, 162, 172
- Optimization (Optimization-class), 136
- Optimization-class, 136
- OptimizationAlgorithm, 47, 56, 69, 80, 82, 138, 141, 145, 166, 171, 172
- OptimizationAlgorithm
 - (OptimizationAlgorithm-class), 137
- OptimizationAlgorithm-class, 137
- optimize, 12, 17–19, 137
- optimize, FedorovWynnAlgorithm-method
 - (optimize), 137
- optimize, MultiplicativeAlgorithm-method
 - (optimize), 137
- optimize, PGBAlgorithm-method
 - (optimize), 137
- optimize, PSOAlgorithm-method
 - (optimize), 137
- optimize, SimplexAlgorithm-method
 - (optimize), 137
- package-PFIM (PFIM-package), 8
- parametersForComputingGradient, 15, 138
- parametersForComputingGradient, Model-method
 - (parametersForComputingGradient), 138
- PFIM (PFIM-package), 8
- PFIM, (PFIM-package), 8
- PFIM-package, 8
- PFIMProject, 18, 48, 59, 71, 72, 74, 82, 83, 147, 151, 166
- PFIMProject (PFIMProject-class), 139
- PFIMProject-class, 139
- PGBAlgorithm, 18
- PGBAlgorithm (PGBAlgorithm-class), 139
- PGBAlgorithm-class, 139
- plot, 18
- PlotEvaluation, 18
- PlotEvaluation (PlotEvaluation-class), 140

- plotEvaluation, 140
- plotEvaluation, Evaluation-method (plotEvaluation), 140
- PlotEvaluation-class, 140
- plotFrequencies, 140
- plotFrequencies, FedorovWynnAlgorithm-method (plotFrequencies), 140
- plotFrequencies, Optimization-method (plotFrequencies), 140
- plotOutcomesEvaluation, 11, 141
- plotOutcomesEvaluation, Design-method (plotOutcomesEvaluation), 141
- plotOutcomesGradient, 11, 142
- plotOutcomesGradient, Design-method (plotOutcomesGradient), 142
- plotRSE, 18, 142
- plotRSE, PFIMProject-method (plotRSE), 142
- plotSE, 18, 143
- plotSE, PFIMProject-method (plotSE), 143
- plotSensitivityIndice, 143
- plotSensitivityIndice, Evaluation-method (plotSensitivityIndice), 143
- plotShrinkage, 18, 144
- plotShrinkage, PFIMProject-method (plotShrinkage), 144
- plotWeights, 17, 18, 144
- plotWeights, MultiplicativeAlgorithm-method (plotWeights), 144
- plotWeights, Optimization-method (plotWeights), 144
- PopulationFim, 18
- PopulationFim (PopulationFim-class), 145
- PopulationFim-class, 145
- Proportional, 19, 145
- Proportional (Proportional-class), 145
- Proportional-class, 145
- PSOAlgorithm, 19
- PSOAlgorithm (PSOAlgorithm-class), 146
- PSOAlgorithm-class, 146
- Report, 12, 18, 146
- Report, Evaluation-method (Report), 146
- Report, Optimization-method (Report), 146
- reportTablesAdministration, 11, 147
- reportTablesAdministration, Design-method (reportTablesAdministration), 147
- reportTablesDesign, 11, 147
- reportTablesDesign, Design-method (reportTablesDesign), 147
- reportTablesFIM, 10, 13, 19, 148
- reportTablesFIM, BayesianFim-method (reportTablesFIM), 148
- reportTablesFIM, IndividualFim-method (reportTablesFIM), 148
- reportTablesFIM, PopulationFim-method (reportTablesFIM), 148
- reportTablesModelError, 15, 149
- reportTablesModelError, Model-method (reportTablesModelError), 149
- reportTablesModelParameters, 15, 149
- reportTablesModelParameters, Model-method (reportTablesModelParameters), 149
- reportTablesPlot, 12, 150
- reportTablesPlot, Evaluation-method (reportTablesPlot), 150
- reportTablesSamplingConstraints, 150
- reportTablesSamplingConstraints, Design-method (reportTablesSamplingConstraints), 150
- resizeFisherMatrix, 12, 151
- resizeFisherMatrix, ANY-method (resizeFisherMatrix), 151
- run, 12, 18, 151
- run, Evaluation-method (run), 151
- run, Optimization-method (run), 151
- SamplingTimeConstraints, 19, 24, 47, 68, 71, 78, 79, 91, 178
- SamplingTimeConstraints (SamplingTimeConstraints-class), 152
- SamplingTimeConstraints-class, 152
- SamplingTimes, 19, 176, 177
- SamplingTimes (SamplingTimes-class), 152
- SamplingTimes-class, 152
- setAdministrations, 10, 153
- setAdministrations, Arm-method (setAdministrations), 153
- setArm, 11, 153
- setArm, Design-method (setArm), 153
- setArms, 11, 13, 154
- setArms, Design-method (setArms), 154
- setArms, OptimizationAlgorithm-method (setArms), 154
- setcError, 16, 154

- setcError, ModelError-method
(setcError), 154
- setContent, 14, 155
- setContent, LibraryOfModels-method
(setContent), 155
- setDataForArmEvaluation, 155
- setDataForArmEvaluation, Arm-method
(setDataForArmEvaluation), 155
- setDataForModelEvaluation, 156
- setDataForModelEvaluation, ModelAnalytic-method
(setDataForModelEvaluation), 156
- setDataForModelEvaluation, ModelAnalyticInfusion-method
(setDataForModelEvaluation), 156
- setDataForModelEvaluation, ModelAnalyticInfusionSteadyStateFIMResults, Optimization-method
(setDataForModelEvaluation), 156
- setDataForModelEvaluation, ModelAnalyticSteadyState-method
(setDataForModelEvaluation), 156
- setDataForModelEvaluation, ModelODEBolus-method
(setDataForModelEvaluation), 156
- setDataForModelEvaluation, ModelODEDoseInEquation-method
(setDataForModelEvaluation), 156
- setDataForModelEvaluation, ModelODEDoseNotInEquation-method
(setDataForModelEvaluation), 156
- setDataForModelEvaluation, ModelODEInfusionDoseInEquation-method
(setDataForModelEvaluation), 156
- setDerivatives, 16, 157
- setDerivatives, ModelError-method
(setDerivatives), 157
- setDescription, 14, 157
- setDescription, Model-method
(setDescription), 157
- setDesigns, 158
- setDesigns, Optimization-method
(setDesigns), 158
- setDistribution, 17, 158
- setDistribution, ModelParameter-method
(setDistribution), 158
- setDose, 10, 159
- setDose, Administration-method
(setDose), 159
- setEquation, 16, 159
- setEquation, ModelError-method
(setEquation), 159
- setEquations, 14, 160
- setEquations, Model-method
(setEquations), 160
- setEquationsAfterInfusion, 16, 160
- setEquationsAfterInfusion, Model-method
(setEquationsAfterInfusion), 160
- setEquationsDuringInfusion, 16, 161
- setEquationsDuringInfusion, Model-method
(setEquationsDuringInfusion), 161
- setEvaluationFIMResults, 18, 161
- setEvaluationFIMResults, Optimization-method
(setEvaluationFIMResults), 161
- setEvaluationInitialDesignResults, 18, 162
- setEvaluationInitialDesignResults, Optimization-method
(setEvaluationInitialDesignResults), 162
- setFim, 11, 162
- setFim, Design-method (setFim), 162
- setFimTypeToString, 13, 163
- setFimTypeToString, Fim-method
(setFimTypeToString), 163
- setFisherMatrix, 12, 163
- setFisherMatrix, Fim-method
(setFisherMatrix), 163
- setFixedEffects, 12, 164
- setFixedEffects, Fim-method
(setFixedEffects), 164
- setFixedMu, 17, 164
- setFixedMu, ModelParameter-method
(setFixedMu), 164
- setFixedOmega, 17, 165
- setFixedOmega, ModelParameter-method
(setFixedOmega), 165
- setInitialConditions, 10, 14, 165
- setInitialConditions, Arm-method
(setInitialConditions), 165
- setInitialConditions, Model-method
(setInitialConditions), 165
- setIterationAndCriteria, 166
- setIterationAndCriteria, OptimizationAlgorithm-method
(setIterationAndCriteria), 166
- setModel, 18, 166

- setModel, PFIMProject-method (setModel), 166
- setModelError, 14, 167
- setModelError, Model-method (setModelError), 167
- setModelFromLibrary, 14, 167
- setModelFromLibrary, Model-method (setModelFromLibrary), 167
- setMu, 11, 13, 17, 168
- setMu, Distribution-method (setMu), 168
- setMu, ModelParameter-method (setMu), 168
- setName, 10, 11, 13, 14, 168
- setName, Arm-method (setName), 168
- setName, Design-method (setName), 168
- setName, Model-method (setName), 168
- setNumberOfArms, 11, 169
- setNumberOfArms, Design-method (setNumberOfArms), 169
- setOdeSolverParameters, 14, 169
- setOdeSolverParameters, Model-method (setOdeSolverParameters), 169
- setOmega, 11, 13, 17, 170
- setOmega, Distribution-method (setOmega), 170
- setOmega, ModelParameter-method (setOmega), 170
- setOptimalDesign, 171
- setOptimalDesign, OptimizationAlgorithm-method (setOptimalDesign), 171
- setOptimalWeights, 17, 171
- setOptimalWeights, MultiplicativeAlgorithm-method (setOptimalWeights), 171
- setOptimizationResults, 17, 172
- setOptimizationResults, Optimization-method (setOptimizationResults), 172
- setOutcome, 9, 13, 19, 172
- setOutcome, Administration-method (setOutcome), 172
- setOutcome, SamplingTimes-method (setOutcome), 172
- setOutcomes, 14, 173
- setOutcomes, Model-method (setOutcomes), 173
- setOutcomesEvaluation, 11, 173
- setOutcomesEvaluation, Design-method (setOutcomesEvaluation), 173
- setOutcomesForEvaluation, 14, 174
- setOutcomesForEvaluation, Model-method (setOutcomesForEvaluation), 174
- setOutcomesGradient, 11, 174
- setOutcomesGradient, Design-method (setOutcomesGradient), 174
- setParameters, 11–14, 17–19, 175
- setParameters, Distribution-method (setParameters), 175
- setParameters, FedorovWynnAlgorithm-method (setParameters), 175
- setParameters, Model-method (setParameters), 175
- setParameters, MultiplicativeAlgorithm-method (setParameters), 175
- setParameters, PGB0Algorithm-method (setParameters), 175
- setParameters, PSOAlgorithm-method (setParameters), 175
- setParameters, SimplexAlgorithm-method (setParameters), 175
- setSamplingConstraintForOptimization, 176
- setSamplingConstraintForOptimization, Design-method (setSamplingConstraintForOptimization), 176
- setSamplings, 19, 176
- setSamplings, SamplingTimes-method (setSamplings), 176
- setSamplingTime, 10, 177
- setSamplingTime, Arm-method (setSamplingTime), 177
- setSamplingTimes, 10, 177
- setSamplingTimes, Arm-method (setSamplingTimes), 177
- setSamplingTimesConstraints, 10, 178
- setSamplingTimesConstraints, Arm-method (setSamplingTimesConstraints), 178
- setShrinkage, 10, 13, 19, 178
- setShrinkage, BayesianFim-method (setShrinkage), 178
- setShrinkage, IndividualFim-method (setShrinkage), 178
- setShrinkage, PopulationFim-method (setShrinkage), 178
- setSigmaInter, 16, 179
- setSigmaInter, ModelError-method (setSigmaInter), 179
- setSigmaSlope, 16, 179

setSigmaSlope, ModelError-method
 (setSigmaSlope), 179

setSize, 10, 11, 13, 180

setSize, Arm-method (setSize), 180

setSize, Design-method (setSize), 180

setTau, 10, 181

setTau, Administration-method (setTau),
 181

setTimeDose, 9, 181

setTimeDose, Administration-method
 (setTimeDose), 181

setTinf, 10, 182

setTinf, Administration-method
 (setTinf), 182

setVarianceEffects, 12, 182

setVarianceEffects, Fim-method
 (setVarianceEffects), 182

show, Design-method, 183

show, Evaluation-method
 (show, Design-method), 183

show, FedorovWynnAlgorithm-method
 (show, Design-method), 183

show, MultiplicativeAlgorithm-method
 (show, Design-method), 183

show, Optimization-method
 (show, Design-method), 183

show, PGBOAlgorithm-method
 (show, Design-method), 183

show, PSOAlgorithm-method
 (show, Design-method), 183

show, SimplexAlgorithm-method
 (show, Design-method), 183

SimplexAlgorithm, 19

SimplexAlgorithm
 (SimplexAlgorithm-class), 184

SimplexAlgorithm-class, 184